

HD oscilloscopes

Teledyne LeCroy has introduced its HDO4000-MS and HDO6000-MS high-definition oscilloscopes, which combine 16 channels of flexible mixed-signal capabilities with



HD4096 high-definition technology, a vast memory and a compact form factor, in bandwidths from 200MHz to 1GHz. All HDO models sport a large 30.73cm (12.1-inch) touchscreen display and an intuitive interface to enhance operation. Powerful debugging tools, plus a full complement of automatic measurements and waveform math capabilities turn the HDO-MS oscilloscope into an all-in-one analogue, digital and serial debugging device. HDO6000-MS oscilloscopes are available in four-channel models and deliver sample rates of 2.5 GS/s; a maximum 250Mpts/channel memory, and bandwidths of 350MHz, 500MHz and 1GHz.

Teledyne LeCroy, Inc., Bangalore
Phone: +91-9972523774
E-mail: sales@teledynelcroy.com
Web: www.teledynelcroy.com

Spectrometer

Shimadzu Corporation has launched a multi-purpose energy dispersive X-ray spectrometer model called EDX-7000/EDX-8000. The combination of high-power X-rays and a high-resolution detector provides good detection limits and high accuracy for any type of material. One of the main strengths of Shimadzu's EDXRF is its powerful software. The analysis is performed by clicking just a single key. The calibration selection, best analysis time, intensity corrections, etc are taken care of automatically by the software. The combination of powerful software and hardware en-

ures detection limits that range from a low ppm to a high percentage. An added advantage is the analysis and measurement of coating thickness on any substrate. The spectrometer can test as many as five layers, with detection ranging from a few nanometers to microns.

Shimadzu Corporation, Mumbai

Fax: (022) 26731869

Phone: 26731868

E-mail: sales@performaxtech.com, pmux@csnl.net

Web: www.performaxtech.com

LEDs & LED LIGHTING

Power LED downlighter

BinayOpto Electronics has launched the 70-CDM power LED downlighter that is designed as a practical light-equivalent replacement for a 70W CDMT (ceramic discharge metal-halide lamp) fitting. With a system power consumption of around 30-35W, this product consumes less than half the power of the CDMT lamp. It has a high colour rendering index of 85 (typical). Available with various options of beam angles, the product is able to form a sharp spot for well-defined illumination. Several colour temperature (CCT) options (such as 3000K, 4000K and 6500K) are available. Other advantages include instant start-on, no infrared or radiated heat output, shock-proof and solid-state construction.

Binay Opto Electronics Pvt Ltd, Kolkata

Phone: +91-33-2210-2039

E-mail: info@binayLED.com

Web: www.binayLED.com

LED slim panel downlight

GSR Infocom has launched an LED slim panel downlight. This product uses an SMD power LED as the light source and can discharge heat rapidly



into the atmosphere. This technology can help to lower the temperature of the spot light, reduce the deterioration of the LED and improve the lifetime of the lamps (life span >40,000 hours). Its features include ultra-thin design conception with just 14mm thickness; it saves energy up to 50-70 per cent, has a high efficiency heat protection system and is driven by a constant current power supply with input AC of 90V to 265V. Other features are an instant start, no flickering, no humming, green environment protection and no RF interference. The company claims that the product has the highest lumens amongst other similar products available in the market.

GSR Infocom Pvt Ltd, New Delhi

Fax: (011) 45024300

Phone: 45024300, +91-9811039262

E-mail: info@gsrinfocom.com

Web: www.indiamart.com/gsrinfocom/

MISCELLANEOUS

Gesture control sensor board

Vishay Intertechnology has launched a gesture control sensor board that supports touchless swipe right, swipe left, proximity and tap control to any device by using a digital proximity sensor and two discrete infrared emitters. The board consists of a Vishay Semiconductors VCNL4020-integrated proximity and ambient light sensor and two of Vishay's VSMF2890RGX01 infrared diodes mounted on either side of the sensor. Sensors that recognise and respond to hand gestures are being designed into consumer products with increasing frequency. Swiping right and left would move to the next or previous page, picture or selection. A tap would be used to make a specific selection and is similar to touching the screen. Pushing in and out zooms in or out, turns the volume higher or lower or changes the back-lighting intensity.

Vishay Components India Pvt Ltd, Bangalore

Fax: (080) 25584291

Phone: 25586277

E-mail: business-asia@Vishay.com

Web: www.vishay.com