



Mrideep Impex Pvt. Ltd.




Thermal Link/Thermal Cutoff/Thermal Fuse



Tf: 76°C-221°C
Ir: 1-40A
Ur: 250VAC

High Current
Tf: 102°C-150°C
Ir: 100-200A
Ur: 250VAC/100VDC
Imax: 100KA-200KA (8/20μs)

Thermal Fuse & MOV (TFMOV)



TFMOV-3Pins TFMOV-5Pins TFMOV21R2P

TFMOV21R3P

Thermal Fuse & MOV (TFMOV). integrate a thermal link and one of two varistors in a single package suitable for SPD Type2 and Type3.
Imax: 3-40KA (8/20μs)

3X TMOVs Inside For SPD Type3
Ir: 7.5KA*3
Energy: 1080J

Surge Protection Device (SPD)



SPD Module (TFMOV+GDT)

For DC48V Power Supplies

Ir: 15KA (8/20μs)
Only 12.6mm Thickness



SPD Module (2TFMOVs+GDT)

For Telecom Power Supplies

Ir: 20KA*2 (8/20μs)
Dual TFMOV with GDT



SM DC Module

For PV Inverter Telecom Power

Uc: 500VDC
Ir: 5KA (8/20μs)
Imax: 10KA (8/20μs)



SM AC Module

For UPS Telecom Power AC Power

Uc: L-N320VAC
L-N-G 385VAC
Ir: 10KA (8/20μs)
Imax: 20KA (8/20μs)



SD Series

For LED Power AC Power UPS

Uc: 385VAC
Ir: 5KA (8/20μs)
Ir: 10KA (8/20μs)

Metal Oxide Varistor (MOV)

UL, TUV, CQC



Imax 1.75-25KA (8/20μs)


Thermal Link & Fusing Resistor (TRXF)



Small Size

1W, 2W 0.27-68Ω

Wire Fusing Resistor (RXF)



0.5W, 1W, 2W, 0.27-68Ω


Glass & Ceramic Tube Fuse (RUSE)

UL, VDE, KTL, PSE
CCC, CQC



Φ5*20mm Φ3.6*10mm
Ir: 200mA-20A
Ur: 250VAC, IR. 35-1500A

Idea Thermal Cut Off (iTCO)



TS-R series

For EV Li-ion Battery Pack
Redundant Protection
100A/100VDC



For Li-ion Battery Pack
60A/100VDC Cutoff Time: 3s
Active Protection, Resettable

Over-Voltage Charge Protector (OVCP)



For LEV Li-ion Battery Pack
15A/100VDC