

primary signal.

Analog Devices India Pvt Ltd, Bengaluru
 Fax: (080) 43002333
 Phone: 43002000/1800-419-0108
 E-mail: cica.asia@analog.com
 Web: www.analog.com

Tunable RF capacitors

Cavendish Kinetics has announced availability of production samples of its tunable RF capacitors to key strategic partners. Use of Cavendish Digital Variable Capacitor (DVC) technology in wireless devices enhances the user experience, differentiates phones and lowers costs for handset makers.


It also improves spectral efficiency, coverage and customer retention for network operators. Potential customers include handset OEMs and ODMs and device module manufacturers. Shipped as a chip scale package (CSP), the DVC is used to tune antennae, power amplifiers and filters to significantly improve RF connection quality and signal strength.

RF tuning is widely viewed as a leading technology solution for today's challenging LTE, LTE-A and 4G wireless standards.

Cavendish Kinetics, Seoul
 E-mail: info@cavendish-kinetics.com
 Web: www.cavendish-kinetics.com

USB 2.0 hub controller chip with battery charging

Renesas Electronics has announced the development of the μ PD720115 USB 2.0 hub controller chip, which supports simultaneous USB communication



and charging of portable devices such as smartphones and tablet PCs via a single USB connector.

The most important feature of the μ PD720115 is its implementation of USB ports with battery charging

functionality which supports the USB battery charging specification, Revision 1.2 (USB BC 1.2).

The μ PD720115 will make it easier to develop products that support simultaneous data communication complying with the USB 2.0 standard and charging portable devices via a single USB connector, such as PCs, digital TVs and charging adaptors. It can help shorten system architecture development cycles and reduce development costs.

Renesas Electronics, Bengaluru
 Fax: (080) 67208777
 Phone: 67208700
 Web: http://sg.renesas.com

TEST & MEASUREMENT

Portable digital pressure calibrator

Fluke Calibration has introduced 3130 portable pneumatic pressure calibrator, a complete system for pressure sensor and pressure gauge calibration, on the bench or in the field.



The 3130 digital pressure calibrator contains everything needed to generate, control and measure pressure, as well as read the output of the device under test. It includes an onboard pressure sensor with a full scale of 2 MPa (300 psi, 20 bar) and an accuracy of 0.025 per cent reading plus 0.01 per cent FS.

The portable pressure calibrator features an internal, motorised pump providing an easy, efficient alternative to time consuming, tiring hand pumps. For applications that involve filling a large volume with pressure, the 3130

allows for connection to an external gas supply, such as compressed plant air or gas cylinder, to supply pressure up-to-300 psi. The pressure can be fine-tuned using the variable volume.

TTL Technologies Pvt Ltd, Bengaluru
 Phone: (080) 25260646/25251859
 E-mail: sudeep.zachuriah@fluke.com
 Web: www.fluke.com/india

Hand-held spectrum analyser

Anritsu Company has announced its MS2720T Spectrum Master hand-held spectrum analyser with option 709 (frequency coverage from 9 kHz to 9 GHz) which has been self-certified by Anritsu to comply with the National Radio Systems Committee (NRSE) requirements for conducting AM and FM broadcast measurements.

The certification verifies that the MS2720T is capable of conducting AM and FM broadcast-proofing measurements, and gives field engineers and technicians greater confidence that their measurements are in compliance.

The MS2720T Spectrum Master is the only hand-held spectrum analyser that has the necessary phase noise and dynamic range to conduct highly accurate broadcast-proofing measurements. Dynamic range is >106 dB in 1 Hz RBW and phase noise is -112 dBm at 10kHz offset at 1 GHz.

Anritsu India Private Limited, Bengaluru
 Fax: (080) 40581301
 Phone: 40581300
 Web: www.anritsu.com

Multi-point CT type energy power meter

Netvox Technology has announced world's first 7-channel CT-Z-821

