

RX200 MCUs for High-performance, Power-efficient Applications



RX200 Flash MCUs bring new levels of capability and performance to ultra-low-power, low-voltage embedded-system applications. Based on the fast 32-bit RX CPU core, they deliver more performance on far less power than other MCUs.



Low Power Architecture

- **Ultra-low voltage operation**
 - 1.62V operation @ up to 20MHz, 31 DMIPS
- **Low power consumption**
 - 130µA/DMIPS (run mode), 1.3µA with RTC on 0.45µA with RTC off
- **High performance**
 - 1.56 DMIPS/MHz,
 - 78 DMIPS @ 50MHz
 - Wide range of voltage operation (1.62V to 5.5V)

Advanced Features

- **Zero wait-state Flash**
 - 2KB block size
 - Programmable at 1.62V
 - Data flash programmable while code is executed (BGO)
- **Scalable**
 - 48-145 pin, QFP, LGA, QFN
 - 32KB-1MB
 - Multifunction pin controller
- **Safety**
 - Complies with IEC60730 Standard

Line up

- **RX220 Group**
 - Maximum 32 MHz
 - 32-256KB memory, LQFP 48-100 pin
- **RX210 Group**
 - Maximum 50MHz
 - 64KB-1MB memory, 48-145 pin
- **RX21A Group**
 - Maximum 50 MHz
 - 256-512KB memory, 64-100 pin
 - 24-bit delta-sigma ADC for smart meter