USB 2.0 High speed (480Mbits/s)
to single/dual/quad channel
independent configurable
parallel/serial interface

FTDI Chip

USB MADE EASY
www.ftdichip.com

HARDWIRED TCP/IP SOLUTION

iEthernet W5500 — Chip
: Fast SPI Ethernet Controller
W5500 chip is a Hardwired TCP/IP embedded Ethernet controller that enables easier internet connection for embedded systems using SPI (Serial Peripheral Interface). W5500 suits best for users who need Internet connectivity for application.

130 nm CMOS Technology Chip
Power effiencient and low temperature when operating (45°C)

Module

Network Module
- Plug-In Network Module (Support Auto MDIX)
- Connect to MCU in the main board
- Easy & Quick Hardware design

Serial to Ethernet Gateway Module
- Plug & Play Type Serial to Ethernet Gateway module
  - Adds Network Function Simply and Quickly
  - Provides Firmware Customization

WIZ550io

WIZ127SR



Wi-Fi Module

WizFi210 / WizFi220
– Compact, Ultra-low Power Embedded Wi-Fi Module
- Supports interface (UART or SPI)
- Quick booting time : less than 20msec
- Complies with IEEE802.11b at the speed up to 11Mbps
- Operation Temperature : -40 ~85℃
- Compact Size : 32 x 23.5 x 2.9 (mm)
- CE, FCC, KCC Certified
- Security : WEP, WPA, WPA2-PSK, Enterprise, (EAP-FAST, EAP-TLS, EAP-TTLS, PEAP)
- Limited AP : Supports direct Wi-Fi connection from PC, Labtop, Smart Phone and etc
- Ultra low power through dynamic power management (34μA at the standby mode)

WizFi

U.FL Connector for External Antenna
WizFi210_CON / WizFi220_CON
Built-in Chip Antenna
WizFi210_CA / WizFi220_CA

WizFi250 – Compact 802 11b/g/n AP Module
- Single Band 2.4GHz IEEE 802.11 b/g/n
- Integrated RF power amplifier
- Supports wireless data up to 65Mbits/s
- Supports excellent power management
- Small size suitable for low volume system integration
- Security : WAPI, AES, TKIP, WPA2
- Soft AP mode: supports direct Wi-Fi connection from
- PC, Laptop, Smart Phone and etc
- Operation Temperature : -20 ~ 85℃
- Compact Size : 28 x 20 x 2(mm)


U.FL Connector to External Antenna
PCB Trace Antenna (Pattern Antenna)

WIZnet
www.wiznet.co.kr

EMBEDDED SYSTEMS SOLUTIONS
Total Development Solutions for Embedded Systems

No 37, Embedded Home, 36th Cross,
Rajajinagar 2nd Block, Bangalore – 560010, India
Ph: 91-80-67648835, 91-9886080011(FTDI)
Ph: 91-80-23577924, 91-9845044338 (WIZnet)
sales@embeddedindia.com
www.embeddedindia.com

Chennai: 91-98410 53251
Delhi: 91-98102 60353
Hyderabad: 91-98486 55337
Pune: 91-9326531952

3D Printer Preassembled or DIY Full Kit

Features:
1.Printing area:200x200x100mm
2.New designed hot end version 2.0 with 0.35mm nozzle,easy to disassemble and clean.
3.Perfect extruder with more durable X-carriage printed from 3mm ABS filament.
4.Come with super smooth Borosilicate glass,easy to remove printing parts,print toys with flat bottom.
5.Power supply 12V 29A DC included.

Replicator Dual Head
BIG SIZE PLATFORM



On-Demand 3D Printing Service also available

TFT LCD Module
interfaced MCU like STM32, AVR and 8051
2.4" / 3.2"/ 4.3" / 5" / 7" TFT LCD
Module with Touch & SD Card slot.

AMP TRONICS™
SYSTEMS PRIVATE LIMITED
ISO 9001:2008 Certified Company
6-3-905/B2, Jaffer Alibagh, Somajiguda, Hyderabad - 82, Ph : +91 40 23320240, +91 9440430199
www.amp-tronics.com e-mail : info@amp-tronics.com
DEALERS / DISTRIBUTORS ENQUIRIES SOLICITED

DREDO DIGITECH RENEWABLE ENERGY DEVELOPMENT ORGANISATION
CONTACT - 09964216969 , support@dredo.org
Manufacturer of MPPT Solar PCU

SOLAR PCU INVERTER
DSP BASED PURE SINE WAVE SOLAR INVERTER
DUAL DISPALY FOR PANEL VOLTAGE , CURRENT AND KWHr READING
BOTH ZERO DROP AND MPPT CHARGER BASED
100 % PROTECTION AGAINST MOSFET
DISPALY YOUR BRAND ON FRONT LCD FOR FREE OF COST

ALL MULTI STAGE MPPT PCU AVAILABLE IN BIG TOWER TYPE CABINETS WITH DUAL DISPALY

New launch IGBT based Dsp Inverter upto 10Kva single phase

MPPT Technology battery charger with temperature compensation : Maximum Current Constant Voltage (MCCV) battery charging method. When the battery is discharged or not fully charged, the MPPT action will track the panel impedance and give the maximum current to charge the battery. When the battery voltage is close to full charge voltage, it will reduce the current to keep the battery voltage constant. The current will become zero when the battery voltage is equal or more than the full charge voltage.

12 V - upto 60 amps
24 V - upto 80 amps
48 V - upto 100 amps
96 v - upto 100 amps

SOLAR MPPT CHARGERS

FACTORY
11/1 4 MAIN 13CROSS VIJAYANAGA
MYSORE.KARNATAKA-17
WWW.DREDO.ORG