

TABLE I
A Comparison of Accelerometers from Different Companies

Companies	Part Number	Range	Sensitivity	Output Type	Signal Bandwidth	Voltage Supply (V)
Analog Devices	ADXL325	±5g	156-192mV/g	Analogue	1.6kHz	1.8-3.6
muRata	SCA3100-D07	±6g	650LSB/g	SPI	45Hz	3.3
STMicroelectronics	H3LS331DL	±100g, ±200g, ±400g	≥363mV/g	Digital	≥1.8Hz	2.16-3.6
measurement SPECIALTIES	3052A	±2g - ±100g	±2 g: 8.0-16.0mV/g ±5 g: 4.8-7.2mV/g ±10 g: 2.4-3.6mV/g ±20 g: 1.2-1.8mV/g ±50 g: 0.48-0.72mV/g ±100 g: 0.24-0.36mV/g		1500Hz	2.7-12
Freescale	MMA7361LC	±1.5g, ±6g	±1.5 g: 740-860mV/g ±6 g: 190.6-221mV/g	Analogue	400Hz, 600Hz	2.2-3.6
Bosch Sensortec	BMA355	±2 g, ±4 g, ±8 g, ±16 g	±2 g: 1024 LSB/g ±4 g: 512 LSB/g ±8 g: 256 LSB/g ±16 g: 128 LSB/g	SPI/I ² C	8Hz-1000Hz	1.62-3.6
DAS Co.	MSENS-AC	±2-8g	1mg			10-30
DIS Sensors	QG40	±0.1 g up to ±16 g		Digital	0-400Hz	10-30
BeanAir	AX-3D	±2g, ±10g and ±13g	±2g: 16384 counts/g ±10g: 3277 counts/g ±13g: 2521 counts/g	Digital	0-800Hz	8-28V
D.R. Italia s.r.l.	ACP-T1-H0010	±1g, ±5g, 18g, 100g, 250g & 500g	< 2%	Analogue		0.5-4.5

TABLE II
A Comparison of Gyros from Different Companies

Companies	Part Number	Range	Sensitivity	Output Type	Signal Bandwidth	Voltage Supply (V)
Analog Devices	ADXRS453	±300 - ±400°/s	80 LSB/°/s	Digital/ SPI	775Hz	3.15-5.25
muRata	SCC1300-D04	±300°/s, ±6g	18LSB/(°/s), 650LSB/g	Digital/ SPI	50Hz, 45Hz	3.3 Digital
STMicroelectronics	L3GD20H	±245 ±500 ±2000°/s	8.75 17.50 70.00mdps/digit	Digital	757.6Hz	3.0
Freescale	FXAS21000	±200/±400/±800/±1600°/s	0.2 0.1 0.05 0.025dps/LSB	SPI	200Hz	1.6-3.6
Bosch Sensortec	BMI055	±125°/s, ±250°/s, ±500°/s, ±1000°/s, ±2000°/s	±125°/s: 262.4 LSB/°/s ±250°/s: 131.2 LSB/°/s ±500°/s: 65.6 LSB/°/s ±1000°/s: 32.8 LSB/°/s ±2000°/s: 16.4 LSB/°/s	SPI	8Hz-1000Hz	2.4-3.6
DAS Co.	MSENS-GY	±300°/s				10-30Vdc
measurement SPECIALTIES	11206AC	±50°/sec - ±600°/s	0.2 °/sec/g	Digital	100Hz	8.5-36
Advanced Sensors Calibration	ASC 261	100 °/sec., 300 °/sec. & 1500 °/sec			150Hz	8-20Vdc
InvenSense	MPU-3300	±225°/sec, ±450°/sec	145.6LSB/°/sec, 72.8LSB/°/sec	SPI or I ² C		2.375V to 3.46V
Texas Sensors	GYRN-P- 3 axis	±50, ±100, ±150 °/s		Digital		5 to 16 V