

pressed, allowing this amplifier to achieve a maximum offset voltage of $4\mu\text{V}$ and a DC to 10Hz input noise voltage of 200nV/PP (typ).

The LTC2057's self-calibrating circuitry results in low offset voltage drift with temperature, $0.015\mu\text{V}/^\circ\text{C}$ (max), and zero drift over time. The amplifier also features an excellent power supply rejection ratio (PSRR) of 160dB and a common mode rejection ratio (CMRR) of 150dB (typ).

The LTC2057 provides rail-to-rail output swing and an input common mode range that includes the V- rail. In addition to low offset and noise, this amplifier features a 1.5MHz (typ) gain-bandwidth product and a $0.45\text{V}/\mu\text{s}$ (typ) slew rate.

Wide supply range, combined with low-noise, low-offset, and excellent PSRR and CMRR make the LTC2057 and LTC2057HV well suited for high dynamic-range test, measurement and instrumentation systems.

Linear Technology India, Bengaluru

Ph: (080) 40124610

E-mail: indiasales@linear.com

Web: www.linear.com

USB port power controllers

Microchip Technology Inc., a leading provider of microcontroller, mixed-signal, analogue and Flash-IP solutions, has expanded its programmable USB port power controller portfolio with the three-member UCS100X family. These new power controllers offer advanced USB-based charging capabilities for designing host devices, such as laptops, tablets, monitors, docking stations and printers as well as dedicated AC-DC power-supply and charging products, such as wall adaptors.

The new USB port power controllers—the UCS1001-3, UCS1001-4 and UCS1002-2—offer high current and priority charging for smartphones and tablets. The UCS100X have also added support for active cables, such as the Apple Lightning connector, along with 12W charging. The UCS1002-2 features a built-in current sensor that can report on the amount of charging current. This allows a system to optimise its

12W USB Port Power Controllers



charging current and appropriately allocate power.

Additionally, the UCS100X can support future USB product designs via a flexible method for detecting and creating charging emulation profiles. This allows designers to update their systems as new products are introduced to the market, while providing compatibility with a wider range of existing products.

Microchip Technology Inc., New Delhi

Fax: (011) 51608632

Ph: 41608631

E-mail: www.microchipdirect.com

Thin-film chip resistor arrays

Vishay Intertechnology Inc. has launched Beyschlag ACAS 0612 precision resistor array, which is ideally suited for precision analogue circuit, voltage divider, feedback circuit and signal conditioning applications that require extraordinarily stable fixed resistance ratios.



With Beyschlag ACAS 0612, Vishay enhanced its ACAS 0612 precision thin-film chip resistor arrays with tighter absolute TCR down to ± 10 ppm/K relative TCR down to ± 5 ppm/K, and relative tolerance down to ± 0.05 per cent for automotive, industrial and telecommunications applications.

The device delivers stable performance for automotive electronics, including engine control units; gear box controls; information, safety, power

supply, body electronics, and braking systems; industrial electronics, such as energy management, measurement control, steering technology, sensors, scales, and bridged and precision amplifiers; and telecommunication base stations.

Vishay Components India Pvt Ltd, Bengaluru

Fax: (080) 25584291

Ph: 25586277

E-mail: business-asia@Vishay.com

Web: www.vishay.com

TOOLS & EQUIPMENT

All-in-one rework station

Den-on Instruments Co. Ltd, Japan, has launched an all-in-one rework system model, RD500V series. RD500V series is suitable for stable, safe rework of large or small boards and large or small sensitive components.



It is a semi-automated single motorised Z-axis placement and reflow station for all types of components rework. The machine uses a high 3-point heating system with an advanced computer control technology designed for safe lead-free and eutectic rework application.

Its three-stage heating system provides 5.6kW overall thermal output for sufficient thermal capacity and control to execute precise profile on small to medium sized boards up to 500×700 mm.

Each system comes complete with a trouble-free controller, Internal Flash memory hard drive, and no hard drive or separate computer is necessary.

RD-500V's full vision optics with a 2MP high-definition video camera and five separate thermocouple inputs make it the ultimate solution for safe, repeatable removal, alignment, placement and soldering of BGAs, CSPs, ultra-fine-pitch QFPs, QFN, 01005