



Ultra-Low $R_{DS(ON)}$ Protected MOSFETs

Integrated IPS

Part Number	Topology	Package	Operating	Max $R_{DS(ON)}$ @ 25°C	Over-current shutdown	Over-temperature shutdown
AUIR3320	High-side driver with current sense	D ² PAK-5 leads	6-26V	4 mΩ	10-55A	165°C

The IR Advantage:

- Full featured protection
- $R_{DS(ON)}$ as low as 0.75 mΩ
- Diagnostic
- Automotive Qualified

IPS Gate Driver

Part Number	Topology	Package	Operating voltage	Output voltage	Special feature
AUIR3200S	High-side driver	SO-8	6-36V	5.7V	Over-current protection Over-temperature protection

Key Applications:

- Battery switch
- Relay Replacement
- Electrical Heater

Logic Level MOSFETs

Part Number	Package	V_{BRDSS} (V)	Max $R_{DS(ON)}$ @ 6V _{GS} (mΩ)	I_D Max @ TC = 25°C (A)	Q_g Typ. @ 4.5VGS (nC)
AUIRLS3034-7P	D ² PAK-7P	40	1.5	380	120
AUIRLS3034	D ² PAK	40	1.8	343	108

For more information, please visit us at www.irf.com or www.irf.com.cn

International
IR Rectifier
THE POWER MANAGEMENT LEADER