



ICs for DC/DC Converter / 2 or 4 Output Channels Power Supply IC Series Contribute to Cost Reduction, Size Reduction, Power Saving


Features and advantages

- BOM Reduction - Reduce number of components by one half



■ Ultra Low Power Mode


Comparing Circuit Current
(MCU+LDO at low power consumption mode)



■ Start-up Sequence

Built in sequencing function and protection function

- (1) ch1 --> ch2
- (2) ch2 --> ch1
- (3) same time



- * SHDNB1/SHDNB2 : On/Off pins.
- * Shutdown starts at the same time

■ Product Lineup

Ch	Typ	I _o	RAA230211	RAA230212	RAA230213	RAA230214	RAA230215
1	SW	3A	1.8V	2.7V	3.0V	3.3V	Variable
2	LDO	0.5A	1.8V	2.7V	3.0V	3.3V	

Ch	Typ	I _o	RAA230401	RAA230402	RAA230403	RAA230404	RAA230405	RAA230406	RAA230407	RAA230408	RAA230409
1	SW	0.5A	1.8V	2.5V	3.0V	3.3V	1.8V	2.5V	3.0V	3.3V	Variable
2	LDO	0.1A	1.8V	2.5V	3.0V	3.3V	1.8V	2.5V	3.0V	3.3V	
3	SW	1.5A			3.3V				Variable		
4	SW	1.5A									

Variable or fixed (1.2V) * selectable by CTL4 pin