

NEW PRODUCTS

RECENTLY INTRODUCED IN INDIA, FROM NEAR AND FAR

COMPONENTS

High-energy capacitor

Vishay Intertechnology Inc. has introduced a wet tantalum high-energy capacitor with a low maximum ESR down to 0.025Ω at $+25^\circ\text{C}$ and 1 kHz, and the highest capacitance of any similar device in the market. Manu-



factured to withstand high stress and hazardous environments, HE4 features a unique case design for improved reliability and performance in military and aerospace applications. It utilises Vishay's proven SuperTan hybrid cathode technology in combination with industry-leading anode designs to achieve its low ESR.

Vishay Components India Pvt Ltd, Bengaluru
Ph: (080) 25586277

E-mail: business-asia@Vishay.com
Web: www.vishay.com

Ultra-wideband high linearity mixer

Linear Technology has launched LTC5510, a high-performance mixer with a very wide frequency range, extending to 6 GHz. It provides a continuous 50-ohm matched input from 30 MHz to 6 GHz, while delivering outstanding linearity and gain flatness. These



features enable applications to work over a wider frequency span without needing to rematch the input for different frequency bands, thereby reducing cost and simplifying design. Additionally, LTC5510's output can reach up to 4.5 GHz, allowing the device to be used either as an up-conversion or down-conversion mixer, making it highly versatile.

Linear Technology India, Bengaluru

Ph: (080) 40124610

E-mail: snayak@linear.com, dawn@linear.com

Web: www.linear.com

Motor drivers

Texas Instruments (TI) has expanded its automotive motor driver family with the introduction of three new devices in the DRV32xx-Q1 family, which now comprises four 3-phase, brushless, pre-FET motor drivers equipped with built-in diagnostic capabilities. The DRV3202-Q1 offers automotive system designers integrated power management and a CAN interface to help reduce board space and design complexity in safety-critical applications. DRV3203-Q1 and DRV3204-Q1 series help customers design safety-critical applications to meet ASIL-B. The three new motor drivers provide designers with highly reliable and space-saving options, helping them address the challenges of harsh conditions such as high-temperature, low-voltage start-stop and cold crank situations.

Texas Instruments, Gurgaon

Phone: +91-8041381665

E-mail: tiasia@ti.com

Repetitive surge protectors

STMicroelectronics has launched the STRVS series of repetitive voltage surge-protection devices. The STRVS' clamping voltage is constant for any load, which enhances the safety of the protected power components



compared with RC (resistor-capacitor) snubber protection.

The stand-off voltage is specified as $I_{IRM}=1 \mu\text{A}$ and $T_J=25^\circ\text{C}$. Under these conditions, the device still acts as an open circuit. The breakdown voltage corresponds to the voltage from which the STRVS starts to go into the avalanche region. This parameter is specified as $I_{IBR}=1 \text{ mA}$ and $T_J=25^\circ\text{C}$.

STMicroelectronics, New Delhi

Web: www.st.com

8-bit MCUs optimised for motor control

EDOM Technology, a professional IC distributor, has introduced Silicon Labs' new C8051F85x/6x MCUs in India. These are highly integrated, 8-bit microcontrollers (MCUs) optimised for cost-sensitive motor control applications. The C8051F85x/6x MCUs combine best-in-class analogue and communications peripherals, Flash sizes ranging from 2 kB to 8 kB, high performance, small-footprint packaging and cost-effective pricing, making them ideal for brushless DC motor control applications used in remote-control helicopters and cars, PCs and electric fans, electric tools and small appliances.

The F85/6x MCUs are a good fit for other consumer and industrial applications such as power supplies, battery chargers, set-top boxes, projectors, lighting equipment and optical transceiver modules. These AEC-Q100-qualified MCUs can also be used in automotive body electronics applica-