



StrongIRFET™ Rugged, Reliable MOSFETs

Specifications

Part Number	$B_{V_{DS}}$	$I_D @ 25^\circ C$	$R_{DS(on)} \max @ V_{GS} = 10V$	$Q_g @ V_{GS} = 10V$	Package
IRFH7004TRPbF	40 V	100 A	1.4 m Ω	134 nC	PQFN 5x6
IRFH7440TRPbF	40 V	85 A	2.4 m Ω	92 nC	PQFN 5x6
IRFH7446TRPbF	40 V	85 A	3.3 m Ω	65 nC	PQFN 5x6
IRF7946TRPbF	40 V	90 A	1.4 m Ω	141 nC	DirectFET Medium Can
IRFS7437TRLpBf	40 V	195 A	1.8 m Ω	150 nC	D ² -Pak
IRFS7440TRLpBf	40 V	120 A	2.8 m Ω	90 nC	D ² -Pak
IRFS7437TRL7PP	40 V	195 A	1.5 m Ω	150 nC	D ² -Pak 7pin
IRFR7440TRPbF	40 V	90 A	2.5 m Ω	89 nC	D-Pak
IRFB7430PbF	40 V	195 A	1.3 m Ω	300 nC	TO-220AB
IRFB7434PbF	40 V	195 A	1.6 m Ω	216 nC	TO-220AB
IRFB7437PbF	40 V	195 A	2 m Ω	150 nC	TO-220AB
IRFB7440PbF	40 V	120 A	2.5 m Ω	90 nC	TO-220AB
IRFB7446PbF	40 V	118 A	3.3 m Ω	62 nC	TO-220AB
IRFP7430PbF	40 V	195 A	1.3 m Ω	300 nC	TO-247

Features:

- Ultra low $R_{DS(on)}$
- High current capability
- Industrial qualified
- Broad portfolio offering

Applications:

- Battery Packs
- Inverters
- UPS
- Solar Inverter
- DC Motors
- ORing or Hotswap

for more information please visit us at www.irf.com or www.irf.com.cn

International
IOR Rectifier
THE POWER MANAGEMENT LEADER