

SVEditor update site, as shown, and select 'OK.' The 'Installation Wizard' will get updated to show the SVEditor feature. By selecting the SVEditor feature and then clicking on 'Next,' you will be prompted to agree to SVEditor's licence (EPL). Simply continue selecting 'Next' until the install process completes.

Updating SVEditor. With a new release every other week (on an average), SVEditor continues to grow and improve. Staying updated with the latest version will only provide you access to the latest features and bug fixes. Updating an Eclipse plug-in is simple. Select the tab 'Help' and click on 'Check for Updates' from the main IDE menu.

Updating SVE. If you have installed one of the SVE packages, updating the SVEditor plug-in will involve a procedure nearly identical to the one explained above. When SVE is installed, the SVEditor plug-in is typically installed by the systems administrator. As a result of this, a normal user cannot update the plug-in. SVE must be started by an administrator in order to update the SVEditor plug-in.

Post installation

Getting started on an SVEditor project. An SVEditor project must be created and configured before editing the source with SVEditor. There are five main steps to setting up an SVEditor project. They are listed below:

1. An Eclipse project around the source must be created
2. Variables must be set to point to




Fig. 2: Setting up an SVE project

the external sources

3. An argument file must be created, in order to specify the root files
4. Specify the SVEditor project properties
5. Rebuild the project and check the results

This step-by-step guide will use the 'UBus' example, provided as part of the UVM package, as an example.

As listed above, the first step in setting up an SVEditor project is to create an Eclipse project around the source to be edited. In the case of this 'UBus' example, the source that we are most interested in is the source for the UBus testbench environment. Begin creating an Eclipse project by selecting New->Project... from the main menu, as shown in Fig. 2.

Expand the 'General' category, if required, and select 'Project.' Next, the project name must be specified and the physical location of the source files selected. To achieve this, follow the steps given below:

1. Specify the project name as 'ubus'
2. The 'Use default location' check box must be unchecked



Fig. 3: Customising linked resources

3. Click the 'Browse' button, select the location and then navigate to the directory where the source is located.

To create the project around the existing UBus source, select 'Finish.' The new UBus project will be shown in the Project Explorer.

Set external-source variables. Most test-bench environments, except a few, use some external components. These could be components that are shared across projects, verification IP, or verification methodology libraries. By defining a variable that points to the external source, these external components could be referenced, which is one of the easiest ways of doing this.

Do note that if an environment variable points to the external component, this particular variable can be used directly. There would be no need to define a variable, as described in this section. The UBus project depends on the UVM library. You must define a variable named UVM_HOME to point to the installation location of the UVM library. We will refer to this variable when specifying the files for SVEditor

THE COMPLETE MAGAZINE ON OPEN SOURCE

OpenSource
ForYou

Your favourite Magazine on Open Source is now on the Web, too.

LinuxForU.com

Follow us on Twitter@LinuxForYou