

COMPONENTS

Driver

Quaser Electronics, under its brand of QLITE, has launched a highly-reliable, active power factor corrected (> 0.95) driver for 24W, constant current 500mA applications. The input voltage range is 110V AC to 265V AC, and the driver size is $101 \times 53 \times 36$ mm. The high efficiency (> 88 per cent) of the driver is maintained by using high-quality driver components. The driver has features like short circuit protection and overload protection.

Quaser Electronics Pvt Ltd

Email: info@qlite.in

Website: www.qlite.in

Power entry module

SCHURTER's power entry module is now equipped with an additional ground line choke to suppress high-frequency interference arising from ground loops on the ground line. The choke also improves asymmetric



attenuation in higher frequencies in medical-filter versions.

The module includes an IEC C14 power inlet connector with a one- or two-pole fuse holder and EMC filter. The series offers current levels from 1A to 10A at 250V AC, according to IEC and UL standards. It has ENEC and cURus approvals and is suited for applications according to IEC 60950. Special filter

versions, M5 and M80, are available for medical devices according to IEC 60601-1. Wiring is done using quick-connect terminals or wire leads. The KFA is compatible with V-lock cord sets, designed to safeguard against unintentional disconnection of power.

SCHURTER Electronics (India) Pvt Ltd

Website: www.schurter.co.in

TEST & MEASUREMENT

Multimeter

GDM-8351 is developed to upgrade the features of the existing 5½-digit digital multimeter, GDM-8251A, at a more competitive price.



New features include fast measurement speed of 320 readings/s, capacitance measurements, 6V high-power LED measurements and USB TMC support. GDM-8351 inherits all good features of GDM-8251A, including VFD dual-display, maximum 120,000 counts, 0.012 per cent basic DC voltage accuracy and USB/RS232C connectors to provide users with measurement precision, lucid data observation and convenient connection with the PC.

GW Instek

Website: www.gwinstek.com

Analyser

CANdoISO is a compact, isolated USB to CAN interface, that allows a PC to be connected directly to an embedded CAN bus. In conjunction with the free CANdo application software, CANdoISO provides a simple, yet powerful means of testing and analysing a CAN network. The free

CANdo SDK allows CANdoISO to be easily integrated into any Windows based program.



The USB and CAN ports are separated by a 500V-rated isolation barrier. This isolation barrier prevents

any harmful ground currents flowing in cases where there is, or maybe, a difference in the ground potential between the PC and CAN bus.

Uchi Embedded Solutions

Email: sales@uchiembedded.co.in

Website: www.uchiembedded.co.in

RF generator and detector

This specialised RF signal generator and detector by Akademika is designed for the education segment, covering a frequency range from 35MHz to 3GHz. It is an accurate and stable product with multiple modes of operation and has modulation capabilities (AM, FM and PSK).

The architecture uses a highly-accurate and stable PLL synthesiser based frequency generator with dou-



ble harmonic suppression capability having low phase noise. The RFGD system employs inbuilt high dynamic log detector arrangement for forward and reflected power measurement. The device is compatible for an external RF sensor probe (50-ohm) and RF antenna to estimate unknown signal mapping. An SMA connector provides output for full span with ad-