

justable output power from -30dBm to +0dBm into a 50Ω load.


BNC-type inputs are available at the rear end of the equipment to connect modulating signals. The system is interfaced with the PC using a USB port and GUI provided on LabVIEW platform to monitor, control and plot records.

Akademika Lab Solutions
Website: www.akademika.in

POWER SUPPLY

Solar hybrid UPS

The smart solar hybrid UPS is built on a DSP based processor with built-in smart features. The product comes with an LCD display that shows not



only voltage and current but also the load consumed in watts from the UPS. It has a built-in integrated charge controller, which is a zero drop current controller.

It automatically selects solar charge option when the sun is out. When the battery is fully charged and the load is on mains and solar charging is possible, it automatically switches to UPS mode and discharges the battery up to 30 per cent and simultaneously charges it on solar power. After the battery is discharged 30 per cent, it again switches back to mains mode automatically. This feature enables power saving when there are no power cuts or when batteries are lying idle.

Elektro Power Systems
Phone: 080-41646969, 22484666

MISCELLANEOUS

Gas leak indicator

Subtronics has introduced industrial gas monitors that offer faster signal processing, higher accuracy and



wider coverage area. These can detect a range of more than 300 gases. Prominent features include three status technology, 100 per cent compatibility with your existing system, PLC, DCS, SCADA or any annunciator panel, flexible mounting options.

Subtronics (India) Pvt Ltd
Email: service@subtronicsindia.com
Website: www.subtronicsindia.com

LAN/WAN module

The RN2483 comes with the LoRaWAN protocol stack, so it can easily connect with the established and rapidly-expanding LoRa Alliance infrastructure, including both privately-managed local area networks (LANs) and telecom-operated public networks, to create low-power wide area networks (LPWANs) with nationwide coverage. This stack integration also enables the module to be used with any microcontroller that has a UART interface, including hundreds of Microchip's PIC MCUs. Additionally, the RN2483 features Microchip's simple ASCII command interface for easy configuration and control.

Microchip Technology Inc.
Website: www.microchip.com

Thermal camera

FLIR has announced the release of FLIR C2, the first full-featured, pocket-sized thermal camera designed to help professionals find

and see hidden heat patterns that can clearly show where problems are, such as sources of overheating electrical connections and more. Its compact and slim design enables the C2 to fit comfortably into any pocket,

The C2's 4800-pixel resolution, high-sensitivity detector captures and displays subtle thermal patterns and small temperature differences useful in electrical and HVAC applications, and a wide 41° field-of-view frames in more of the scene. The C2 includes a built-in worklight and flash that helps illuminate poorly-lit areas, common in various inspection environments. The extra illumination also ensures that a brighter visible photo is able to be captured along with C2's thermal image.

FLIR Systems India Pvt. Ltd
Website: www.flir.com

Wireless battery charger controller

The STWBC digital controller for wireless battery charge (WBC) transmitters from STMicroelectronics offers the most flexible and efficient solution for controlling power transfer from a WBC transmitter (TX) to a receiver (RX) in WBC-enabled phones, wearables and other battery-powered devices that use electromagnetic induction for recharge.

The STWBC performs all essential functions for transmitter control. It can precisely control the amount of transmitted power to match the requirements of the receiving unit in terms of maximising the efficiency of the power transfer and minimising any increase in the operating temperature. The digital feedback between TX and RX units allows detection of metal objects close to the receiver (foreign object detection) that could result in potential disasters, enabling the STWBC to stop power transmission when such objects are detected.

STMicroelectronics
Phone: +91-120-2352999
Website: www.st.com