

COMPONENTS

Integrated gate driver

This integrated gate driver offers adjustable gate drive settings with the flexibility to drive a wide range of external field-effect transistors, supporting multiple motors, speeds or



varying loads. The DRV8701 enables designers to scale their platforms using a single gate driver across various brushed DC motor models in equipment such as white goods, household appliances, robotics and home automation.

Texas Instruments

Website: www.ti.com

AC-DC control IC

The BD7682FJ-LB control integrated circuit (IC) has been designed specifically for SiC MOSFETs in industrial equipment such as servers and other large power applications.



Its key features are:

1. Maximizes SiC MOSFET performance for energy savings
2. SiC MOSFET contributes to miniaturisation
3. Multiple protection circuits support high voltage operations up to 690V AC

ROHM Co. Ltd

Website: www.rohm.com

Automotive high-side drivers

VND7050AJ12 and VND7140AJ12 drivers have minimum supply voltage of 3.2V to keep essential equipment such as dashboard instruments oper-

ating, as the vehicle battery voltage dips during engine cranking. The devices provide a reliable replacement for electromechanical relays and associated circuitry. These have built-in multiplexed current-sense diagnostics that provide precise analogue load-current feedback.

STMicroelectronics

Website: www.st.com

IR camera lens

Compatible with Fluke TiX560 and TiX520 infrared (IR) cameras, the 25 micron macro lens enables technicians to distinguish thermal variations across distances smaller than a human hair, making it ideal for applications in electronics/PCB board research and development or anything requiring near-microscopic-level IR resolution.

Fluke Corp.


Website: www.fluke.com/india



CMOS image sensor

The AR0136AT optical format CMOS digital image sensor with 1280x960 resolution and 3.75 micron BSI pixels supports linear and high dynamic range (HDR) modes on a single chip HDR solution, with a 120dB dynamic range in HDR mode.

It has an output pixel rate of



74.25MP/second (maximum), which results in a frame rate of 45 frames per second (fps) at 960 pixels resolution and 60fps at 720 pixels resolution.

ON Semiconductor

Website: www.onsemi.com

Ferroelectric RAM

MB85RS1MT, an 8-pin wafer-level chip scale package (WL-CSP), occupies only 23 per cent of the mounted surface area of the existing 8-pin small-outline package (SOP) and is roughly one-fifth as thick. WL-CSP ferroelectric RAM (FRAM) is ideal for wearable devices.

Fujitsu Semiconductor Ltd

Website: www.fujitsu.com

TVS diodes

Littelfuse has introduced six new series of high-reliability TVS diodes that are up-screened for use in aerospace applications. The 5KP/15KPA/30KPA-HR and 5KP/15KPA/30KPA-HRA series TVS diodes are designed specifically to protect sensitive electronic equipment from voltage transients induced by lightning surges and other transient voltage events.

Littelfuse Inc.

Website: www.littelfuse.com

Circuit breaker

SCHURTER's circuit breaker, the T12-MSM, is a unique combination of a reliable circuit breaker and a robust metal switch. It offers a variety of design options including an assortment of colours for ring or point illumination, as well as options for standard or custom inscription.

SCHURTER Electronics (India) Pvt Ltd

Website: www.SCHURTER.co.in

Industrial Ethernet communication ICs

Renesas has announced the launch of the R-IN32M4-CL2 industrial Ethernet communication application-specific standard product (ASSP) with integrated gigabit PHY to support the increasing network and factory productivity needs of Industry 4.0. R-IN32M4-CL2 extends the family of R-IN32M3 platform that incorporates hardware accelerators supporting real-time operating system (RTOS)