

Some Thermography Tools available in the Market

Parameters	Product	Field of view	Standard temperature range	Resolution	Sensitivity	Accuracy	Spectral response	Power Supply
FLIR	AX8 thermal imaging camera	48°×37°	-10°C to +150°C (14°F to 302°F)	80×60 pixels	Minimum 10 Lux without illuminator	±2°C (±3.6°F) or ±2% of reading (+10 to +100°C@+10 to +35amb)	Spectral range: 7.5µm-13µm	12/24V DC, 2W continuously/ 3.1W absolute max.
	CM174	38.6°×50.0°	-25°C to 150°C (13°F to 302°F)	4800 pixels (60×80)	—	±5.4°F (3°C) or ±3% of rdg	8µm-14µm	—
	T1K thermal imaging camera	28°×21°	-40°C to +2000°C	—	<0.02°C (at +30°C)	±1°C (±1.8°F) or ±1% at 25°C for temperatures between 5°C to 150°C ±2°C (±3.6°F) or ±2% of reading at 25°C for temperatures up to 1200°C	7.5µm-14µm	—
Fluke	TX1000 IT camera (Models: FLK-TX1000 30Hz Fluke TX1000 IR camera 30Hz (1024×768) and FLK-TX1000 9Hz Fluke TX1000 IR camera 9Hz (1024×768))	32.4°×24.7° (1.0/30mm)	-40°C to 2000°C (-40°F to 3632°F)	1024×768 (786,432 pixels), 2048×1536 (3,145,728 pixels) (super resolution mode)	±0.05°C (at 30°C) target temp (50 mK)	±1.5°C or ±1.5 %	7.5µm-14µm	Externat: 12V DC, 24V DC, Battery: standard li-ion video camera battery
Keysight	U5855A	28° (H) × 21° (V)	-20°C~350°C	Detector resolution 160×120, fine resolution (in-camera) 320×240 (IR pixels)	Range 1: 0.07°C (at 30°C), Range 2: 0.1°C (at 30°C), Range 3: NA	±2°C or ±2% (whichever is greater); at 0°C~40°C ambient temperature	8µm-14µm	Line voltage range: 50/60Hz, 100V AC-240V AC (auto/universal voltage), 1.2A mains supply voltage fluctuations not to exceed ±10% of the nominal voltage, output voltage: 12V DC, 3A, installation category I (Isolated ELV supply source connected to mains through an AC/DC power adaptor)
	U5856A	28° (H) × 21° (V)	-20°C~650°C	Detector resolution 160×120, fine resolution (in-camera) 320×240 (IR pixels)	Range 1: 0.07°C (at 30°C), Range 2: 0.5°C (at 30°C), Range 3: NA	±2°C or ±2% (whichever is greater); at 0°C~40°C ambient temperature	8µm-14µm	Line voltage range: 50/60Hz, 100V AC-240V AC (auto/universal voltage), 1.2A mains supply voltage fluctuations not to exceed ±10% of the nominal voltage, output voltage: 12V DC, 3A, installation category I (Isolated ELV supply source connected to mains through an AC/DC power adaptor)
	U5857A	28° (H) × 21° (V)	-20°C~1200°C	Detector resolution 160×120, fine resolution (in-camera) 320×240 (IR pixels)	Range 1: 0.07°C (at 30°C), Range 2: 0.1°C (at 30°C), Range 3: 0.5°C (at 250°C)	±2°C or ±2% (whichever is greater); at 0°C~40°C ambient temperature	8µm-14µm	Line voltage range: 50/60Hz, 100V AC-240V AC (auto/universal voltage), 1.2A mains supply voltage fluctuations not to exceed ±10% of the nominal voltage, output voltage: 12V DC, 3A, installation category I (Isolated ELV supply source connected to mains through an AC/DC power adaptor)
MECO	IRT380P	—	-50°C~380°C -58°F~716°F	0.1°C/0.1°F	—	±1.5°C	6µm~14µm	9V battery
	IRT550P	—	-50°C~550°C -58°F~1022°F	0.1°C/0.1°F	—	±1.5°C	6µm~14µm	9V battery
	IRT1050P	—	-50°C~1050°C -58°F~1922°F	0.1°C/0.1°F	—	±1.5°C	6µm~14µm	9V battery
Flex	Thermal Camera TG-501	30°	-30°C to 800°C (-22°F to 1452°F)	• Optical resolution: 50:1 (calculated at 95 per cent energy) • Display resolution: 0.1°C (0.2°F)	<0.02°C at +30°C	±1.5°C or ±1.5% of reading ±2.0°C at -10°C to 0°C ±3.0°C at -30°C to -10°C	—	AA x 3 batteries