

Continued from previous page...

LED driver	Short feature	Company name	Feature	Application
AL1791/1792/1793/1794 [AL179x]	Single/dual/triple/quad-channel current-ratio-optimised LED driver with analogue and PWM dimming U-DFN -4030-14	Diodes Inc.	- Input voltage range: 6.5V to 30V 1/2/3/4-channel LED drivers: independent analogue or PWM dimming control for each channel - Reference current: adjustable by an external reference resistor - Ratio-optimised currents for four independent LED channels (AL1794 only suitable for tunable white and tunable colour) - Low standby power: with EN pin - e-flicker-free high-frequency PWM dimming with deep dimming - Capability: supports 10KHz down to 1.0 per cent, 4KHz down to 0.4 per cent or 1KHz down to 0.1 per cent - Internal protections: UVLO, LED string open/short protection - Over-temperature protection: thermal shutdown and auto thermal recovery - Fault reporting: UVLO, over-temperature protection, open and short LED power good reporting - Low system bills of material cost - Ambient temperature range: -40°C to +125°C - Totally lead-free and fully RoHS-compliant - Halogen and antimony free: green device	1-channel dimmable smart connected light (SCL) bulbs 2-channel tunable white SCL bulbs 3-channel tunable white or colour SCL bulbs 4-channel tunable white and colour SCL bulbs - Smart connected LED tubes, panel lights, troffers and ceiling lights
TLD 2314EL	Litix basic (scalable linear current sources family for automotive LED applications)	Infineon	- One to three output channels; typ. 60mA to 180mA - Supply voltage: 5.5V-40V - Integrated protection and diagnostic feature - Stable and reliable LED brightness - PWM via external PWM signal and optional via integrated PWM engine	- Automotive exterior and interior LED lighting - Low to medium power LED applications, for example, position, turn, tail, stop, CHMSL, RCL, reverse, fog or dome
NSI45030 T1G, NSV45030 T1G	Constant current regulator and LED driver 45V, 30mA + 15 per cent, 460mW package	On Semiconductor	- Robust power package: 460mW - Wide operating voltage range - Immediate turn on - Voltage surge suppressing: protecting LEDs - Self Biased Transistor technology - Negative temperature coefficient - NSV prefix for automotive and other applications requiring unique site and control change requirements; - AEC-Q101 qualified and PPAP capable* - Devices are Pb-free, halogen-free/BFR-free and RoHS-compliant	- Automobile: Chevron side mirror markers, clusters, display and instrument backlighting, CHMSL, map lights - AC lighting panels, display signage, decorative lighting, channel lettering - Switch contact wetting
LYT Switch-0, LYT Switch-2, LYT Switch-3	LYTSwitch LED driver ICs	Power Integration	- LYTSwitch-0 family of LED driver ICs is specifically designed for non-isolated non-dimming LED bulbs and T8 tube applications - LYTSwitch-2 LED driver ICs dramatically simplifies low-power constant current LED drivers by eliminating the optocoupler and secondary control circuitry - LYTSwitch-4 Family of LED driver ICs enables off-line LED drivers with high power factor, which easily meet international requirements for THD and harmonics	—

TBS1000B Series Digital Oscilloscopes

SPECIAL OFFER

Performance You Need
at a Price You Can Afford.



70 MHz at Rs.29000



100 MHz at Rs.39000

- 7-inch WVGA display
- Unique TrendPlot™ feature
- Enhanced limit-test feature
- Digital real-time sampling
- 34 automated measurements
- PC Courseware Editor Tool (EDU Series)

Visit: in.tek.com/TBS1000/offer

☎ +91-80-30792726 / 41

✉ india.mktg@tek.com
Tektronix®