

High Performance in the most important test field - the real world



GA40XX Series Spectrum Analyzers


GA40XX series is a small size, light weight, cost-effective portable spectrum analyzer to meet your all the RF application demands. It has easy-to-keyboard layout and high-definition 8.5-inch TFT color LCD display; display contains the appropriate settings and alerts. It includes the standard USB, LAN and RS232 communication interface, virtual terminal display and control and remote network access.

The spectrum analyzer can be widely applied in many fields of science education, enterprise research and development and industrial production.

Features

- Frequency range 9 kHz to 1.5GHz / 3GHz / 7.5GHz
- DANL: <160 dBm (typical value)
- Phase Noise: -100 dBc/Hz (Offset 10 kHz)
- Full amplitude accuracy of <1.0 dB
- Minimum resolution bandwidth (RBW) 1 Hz
- Standard preamplifier
- Tracking generator (optional)
- AM/FM demodulation measurement (optional)
- 8.5-inch (800x480) widescreen
- LAN \ USB Host \ USB Device \ RS232 or VGA

Model Spec	GA4032 GA4032-TG	GA4062 GA4062-TG	GA4033 GA4033-TG	GA4063 GA4063-TG	GA4064 GA4064-TG
Frequency	9kHz - 1.5GHz		9kHz - 3GHz		9kHz - 7.5GHz
Aging rate	±1ppm/year		±0.1ppm/year		±0.1ppm/year
RBW	100Hz to 1MHz, Sequence 1-3-10		100Hz to 1MHz, Sequence 1-3-10		1Hz to 3MHz, Sequence 1-3-10
Phase Noise	<90dBc/Hz @10kHz		<90dBc/Hz @10kHz		<95dBc/Hz @10kHz
DANL	≤ -128dBm -140dBm (Typical)		≤ -128dBm -140dBm (Typical)		≤ -148dBm -160dBm (Typical)




Three simultaneous trace display
at RBW 1M/100K/10K



Waterfall plot display



Adjacent channel power



Distinguish similar nearby signal at RBW 1Hz

Other Products

Vector Network Analyzers

Function Generators

Handheld Scopes

RF Probes

Power Supplies

RF Training Kits

Building A8, 2nd Flr, Tanglang Indl Zone, Xili, Nanshan, Shenzhen, China

+86 755 86021369

gratten@gratten.cn

GRATTEN

NANJING GLARUN ATTEN
TECHNOLOGY CO. LTD.

www.gratten.cn