



NEW!



Waveform capture rate up to 500,000 wfms/s (sequence mode)



Record Length up to 140 Mpts




Eres Mode


INNOVATIVE DESIGN, POWERFUL PERFORMANCE

SDS2000X Super Phosphor Oscilloscope coming.....

- 8 Inch TFT-LCD display
- New generation of SPO technology
- Waveform capture rate up to 140,000 wfms/s (normal mode), and 500,000 wfms/s (sequence mode)
- Record length up to 140 Mpts
- 37 Automatic measurement parameters
- 16 Digital channels (MSO - option)
- Intelligent trigger: Edge, Slope, Pulse, Window, Runt, Interval, Dropout, Pattern and Video
- 10 Types of one-button shortcuts



Sequence Mode



Color Temperature Display



Serial Bus Decoding

Model	SDS2072X SDS2074X	SDS2102X SDS2104X	SDS2202X SDS2204X	SDS2302X SDS2304X
Bandwidth	70 MHz	100 MHz	200 MHz	300 MHz
Real-time Sampling Rate	2G Sa/s			
Memory Depth	140 Mpts			
Trigger Type	Edge, Slope, Pulse width, Window, Runt, Interval, Dropout, Pattern, Video			
16 Digital Channels (MSO Option)	Maximum waveform capture rate up to 500 MSa/s, Record length up to 140 Mpts/CH			
Waveform Generator (Optional)	Single channel, Max. frequency up to 25 MHz, 125 MSa/s sampling rate, 16 Kpts wave length			
I/O	USB Host, USB Device, LAN, Pass/Fail, Trigger Out, GPIB (Optional)			

SIGLENT TECHNOLOGIES CO., LTD.

Add: Blog No.4 & No.5, Antongda Industrial Zone, 3rd Luxian Road, Bao'an District, Shenzhen, 518101, China.
Tel: +86 755 3661 5186; Email: sales@siglent.com; Website: http://www.siglent.com/ens/

