

DC isolation voltage and an operating temperature of -40°C to +85°C.

Mornsun Guangzhou Science & Technology Co. Ltd

Website: www.mornsun-power.com

TEST & MEASUREMENT

Clamp meter

The EX850 TRMS 1000A AC/DC clamp meter for Android has the following key features:

- Integrated Bluetooth connects with most Android devices to transmit readings for remote viewing
- Works with Android app to display large, easy-to-read values for AC/DC voltage, AC/DC current, capacitance, resistance, frequency, diode

test and temperature [(type K and infrared (IR))], up to 10m away

- Non-contact IR thermometer design with laser pointer
- CAT IV safety rating for industrial applications
- True RMS current and voltage measurements
- Peak hold captures inrush currents and transients
- 43mm jaw opening for conductors up to 750MCM or two 500MCM
- 4000-count backlit display
- Auto-ranging with manual range button
- Data Hold, Min/Max and Auto Power Off functions

FLIR Systems India Pvt Ltd

Website: www.flir.com

Selective level meter

The SLM3505 is designed to provide a single-instrument solution for the electric utility system protection engineer and relay/communications technician



responsible for the alignment and maintenance of power-line carrier, audio tone and FSK communication systems.

Key functions of the meter are:

- Single and dual frequency selective level meter
- Impedance analyser (LCR measurements)
- Frequency-response analyser
- VSWR meter
- Signal generator
- Oscilloscope

Aplab Ltd

Website: www.aplab.com

Solar power meter

MECO solar power meter is used for measuring solar power or solar irradiance. It uses high-sensitivity silicon



photodiode to measure solar power. The solar meter can also detect the solar tilt angle with orientation.

This instrument is designed to measure solar power in the range of 400 nanometres to 1100 nanometres and solar power and transmission up to 2000W/m². It has Max/Min/Avg and Data Hold functions to identify locations with maximum or minimum power. The good spectral range, orientation and angular detection of the meter allow users to conduct precise quantitative measurements of solar power radiation.

MECO Instruments Pvt Ltd

Website: www.mecoinst.com

Waveguide mixer

The newly-released MA2808A along with MS2830A in the 26.5GHz/43GHz configuration (MS2830A-044/045) supports development and production of equipment



for both E-band (70GHz/80GHz) wireless backhaul as well as automobile collision avoidance radar (77GHz/79GHz).

MA2808A combines excellent minimum sensitivity performance with a wide measurement span in an easy-to-use configuration to support millimetre-wave measurements.

Anritsu India Pvt Ltd

Website: www.anritsu.com

LEDs

LED fittings

This product is complete for fixing and connection to 230V AC, 122cm (4-feet) fitting, provided with two mounting brackets on both ends that can be used to mount the fitting on any flat surface.



The angle of the tube can be adjusted and locked on the bracket, allowing the light to be directed downwards in case of wall mounting. This allows for greater flexibility in use. The fittings are available in the following models:

Binay Quadralume. 12ES (extra-saving ultra-high efficiency), power consumption 12W, replaces 1x36W fluorescent tube

Binay Quadralume. 16ES (standard efficiency), power consumption 16W, replaces 1x36W fluorescent tube

Binay Quadralume. 24 DUO, power consumption 25W-28W, replaces 2x36W fluorescent tube

Binay Quadralume. 24x2 QUAD-RO double type, power consumption 50W-56W, replaces 4x36W fluorescent tube

Binay Opto Electronics Pvt Ltd

Website: www.binayLED.com