



mixer MA2806A (50GHz to 75GHz) to expand millimeter-wave measurement solutions supported by the company's signal analyser MS2830A.

Connecting MA2806A to MS2830A supports spectrum measurements in 50GHz to 75GHz band (V-band) currently used by various millimeter-wave sensors, WiGig Gigabit Wireless LAN (802.11ad), and broadcast video camera streaming equipment. MA2806A is targeted at development and manufacturing of devices and antennae for these types of equipment.

Anritsu India Pvt Ltd
www.anritsu.com

Airflow anemometer

MECO airflow anemometer (model 961P) is used to measure wind speed and temperature. It acts as an indicator that spins in the wind and gives a direct measure of the speed of the wind. It is mainly used in the HVAC industry for measuring airflow of air-conditioners.

Measuring range for the air flow is 1 ~ 25m/s and for temperature 0 ~ 50°C. The meter is equipped with special functions such as m/sec, ft/min, knots, km ph, MPH, CFM, max./min./hold, and auto power off.

MECO Instruments Pvt Ltd
www.mecoinst.com

Transformer turn-ratio meter

Some features of the product are:

- Fully-automatic measurement of transformer turn ratio



- Excitation current, HV and LV voltage, polarity and per cent deviation measurement
- 36 vector group selection facility
- 3-phase connection enables simpler and faster testing
- 0.1 per cent accurate measurement by 24-bit technology
- 20 x 4 blue LCD to view all parameters on a single screen
- Over-current protection
- Inbuilt memory to store test data
- Portable (tabletop and panel mount)

Veer Electronics
www.veerelectronics.com

LEDs

COB downlights

iLux Electricals has come up with COB downlights that are made from components of Vossloh-Schwabe, Germany.

The downlights have CRI > 85, L90/B10, 3Step Macadam. These are available in 11W, 15W, 18W and 22W.

iLux Electricals Pvt Ltd
info@iluxelectricals.com



LED lights

Philips Piano LED lights are aesthetically inspired by the instrument and its elegant black-and-white colour combination makes spaces appear highly sophisticated. The skillfully-designed pieces of the collection allow users to slide independent modules giving them the freedom to personalise lights. They can adjust the light bars and create patterns based on their choice.

Philips Lighting
www.lighting.philips.co.in



INTERNET OF THINGS

Wireless user-authentication technology platform

STMicroelectronics and ClevX, an intel-

lectual property innovator and technology developer for portable storage and mobile device manufacturers, have announced the world's first DataLock-secured encrypted portable storage media with Bluetooth Smart wireless user authentication.

Users can interact with secure portable storage (full-disk, XTS-AES 256-bit encryption) from their smartphones or wearable devices where all data on the drive is encrypted and can be locked/unlocked using single- or multi-factor authentication.

STMicroelectronics
www.st.com

Module

Microchip has announced RN2483 LoRa module, which is the world's first to pass LoRa Alliance's LoRaWAN certification program. The module was independently tested by Espotel's accredited test laboratory to meet the functional requirements of the latest LoRaWAN 1.0 protocol specification, for operation in 868MHz licence-free band.

Microchip Technology Inc.
www.microchip.com

MISCELLANEOUS

Analogue timers

Shavison has launched 48mm x 48mm panel-mounted timers in analogue timer series. These are available in two operating modes, namely, on delay/interval and cyclic on first or off first, whereas on delay/interval timers are available in four different supply voltage and time ranges, that is, on delay/interval (60 minutes, 230V AC), on delay/interval (60 minutes and 230V AC/110V AC/24V AC/24V DC), on delay/interval (30 hours, 230V AC), on delay/interval (30 hours, universal supply voltage).

Shavison Electronics Pvt Ltd
www.shavison.com

