



FEEDBACK

YOUR SUGGESTIONS

ARTICLES ON ADVANCED CONTROLLERS

I thank EFY team for providing excellent tutorials and website links. I suggest increase in number of pages and introduction of advanced controllers and development boards for learning in each issue. There should be five or more articles on such development boards as BeagleBone, Banana Pi and Intel Galileo boards.

Pamarthi Kanakaraja

Through email

EFY. Thanks for the feedback! We already carry articles based on Arduino and Raspberry Pi. We will certainly keep your views in mind while selecting the articles submitted to us for publication and also while developing new projects in EFY Lab.

AMERICAN CARRIER STRIKE

In 'American Carrier Strike Groups: An Electronic Perspective' published in September 2015 issue, on page 74, under 3D air-surveillance radar section, regarding 3D surveillance radar it is mentioned that computer-controlled planar-array radar varies its frequency instead of nodding the antenna up and down.

It is wrong! The nodding action of the beam is achieved by the phase shift method of the array and not by changing the frequency.

Vijesh C.N.

Through email

The author B. Kamalanath replies: What the reader has mentioned is true for radars where the RF energy is fed in parallel to the transmitter elements such as in AN/SPY-1 radar (explained under the section in the second part of the article). Here, the phase of the parallelly fed signals will be varied to form a wavefront in the

desired direction.

But the AN/SPS-48 radar (mentioned in the article) uses frequency scanning. That is, the RF energy is series fed to the transmitter elements.



FROM FACEBOOK

EFY's Electronics Design Community

I took Electronics as a subject while in the Army from 1967 to 1970 here in the United States. One of the things I missed the most was the famous electronics magazines like Popular Electronics and Radio Electronics. I want to thank you for picking up where they left off. I enjoy your publication very much.

Steve Griffith

EFY is great! Just increase the number of articles in Do-It-Yourself section and videos in the accompanying DVD.

Neeraj Prasher

'Spot An Error' AWARD Winners

In Innovation section, in 'A One-Stop Shop for Custom-Made LTE Stack' article published in November 2015 issue, under technical specifications the acronyms for FDD and TDD are incorrectly mentioned as Frequency Division Multiplexing and Time Division Multiplexing instead of Frequency Division Duplex and Time Division Duplex, respectively.

Siddharth Koul

In 'ATmega16A Based GPS Receiver' DIY article published in November 2015 issue, the statement 'GPS receiver used for this prototype is a marine GPS receiver MR-600 and a sunrom GPS receiver (1216) with an active antenna' is wrong. It gives the impression that both the receivers are required but, actually, either one should suffice.

Deepak Nair

Corrections

In 'Automatic USB-Controlled Power Switch' DIY article published in November 2015 issue, in Fig. 3, the D+ and D- terminals of CON4 should be interchanged.
Bhenkateswar Mahanta

In 'FreeRTOS on PIC18F4520 MCU' DIY article published in November 2015 issue, under Application of FreeRTOS running on an MCU section, the R00, R01 and R02 pins are not for Port B. These are the pins on Port D.
Rishad P.K.

EFY. Thanks for pointing out the mistakes! But regret inability to include under 'Spot an Error' award category since the emails were received after the deadline.

Due to this, the wavefront is changed by changing the frequency of the RF energy and not by changing the phase.

OBJECT COUNTER

In the source code of 'AVR Based Programmable Object Counter' DIY project published in August 2015 issue, the `#define F_CPU 8000000` line is missing. Also, the default clock frequency or on-chip oscillator frequency of AVR (ATmega16) is 1MHz. To access the external oscillator we have to change the fuse bits, which is not mentioned anywhere in the article.

Visweswara Rao

Through email

The author Ashutosh M. Bhatt replies:

It is not required to include the line `#define F_CPU 8000000` anywhere in the source code. Actually, the AVR Studio compiler tool takes care of all the issues regarding clock frequency. It generates hex code relevant to selected crystal frequency. You may select desired clock frequency as per your crystal connected in the circuit. If you buy a new ATmega8/16/32 microcontroller then it is required to program the fuse bits for the external crystal.