

plication processors via various standard interfaces, such as single or dual OpenLDI flat panel display links and DRGB888. The fully-integrated high-speed APIX2 transmitters, with a downlink data rate of 3Gbps and an uplink rate of 187.5Mbps, allow up to three high-resolution remote displays to be connected in parallel.

Socionext Inc.

Website: www.socionext.com

Power management IC

ROHM recently announced the development of a high-efficiency power-management IC optimised



for Freescale Semiconductor's i.MX 6SoloLite applications processor.

ROHM's BD71805MWV utilises power supply technology cultivated for mobile applications to optimise circuit configuration for the i.MX 6SoloLite processor. The result is significantly reduced power consumption during both standby and normal operation, prolonging battery life considerably.

ROHM Co. Ltd

Website: www.rohm.com

Microcontroller

Renesas has announced the RL78/G1F group of multi-function microcontrollers (MCUs). Featuring enhanced peripheral functions and compatibility across the RL78/G1x series of MCUs, the new devices simplify sensorless brushless DC motor (BLDC motor) control and deliver precision operation at faster rotational speeds with high accuracy for energy-efficient home appliances and electric power tools.

Renesas Electronics Corp.

Website: www.renesas.com

System on chip

MediaTek Helio P10 is a high-performance, high-value system on chip focused on the growing demand for slim form factor smartphones that provide premium, flagship features. It showcases 2GHz, true octa-core 64-bit Cortex-A53 CPU and 700MHz, dual-core 64-bit Mali -T860 GPU.

MediaTek Inc.

Website: www.mediatek.com

Piezo switch

The PSE HI piezo switches from Schurter Electronics have an ingress protection class rating of IP67. The hermetic seal makes the switches ideal for use in areas that must be regularly cleaned or disinfected.

The switches offer a robust metal housing, well-suited for use in harsh environments. The impact resistance according to DIN EN 50102 is IK06.

SCHURTER Electronics (India) Pvt Ltd

Website: www.SCHURTER.co.in

Embedded flash memory

Microchip Technology, through its Silicon Storage Technology (SST) subsidiary, and GLOBALFOUNDRIES, has announced SST's 55nm embedded SuperFlash non-volatile memory (NVM) on GLOBALFOUNDRIES' 55nm Low Power Extended (LPx)/RF-enabled platform. The technology meets JEDEC standards and the requirements of AEC-Q100 grade I qualification with an ambient temperature range of -40°C to 125°C and endurance of 100k program/erase cycles with more than 20 years of data retention at 150°C.

Microchip Technology Inc.

Website: www.microchip.com

T&M

Oscilloscope

The deep memory digital storage oscilloscope from MetroQ has the following features:

Ultra-thin. Minimum 7cm

Super-light. 1.8kg

Storage depth. Maximum 10M

Display extension. SVGA output
LAN. Network data sharing

Metro Electronic Products

Website: www.metroQ.in

Digital clampmeter

MECO-G has introduced a new series of handheld 3½-digit clampmeters with back-light LCD display. These can measure AC voltages, DC voltages, AC current, resistance, capacitance, temperature and frequency.

Additional features like diode test, transistor check, continuity check, low battery display, data hold and auto power off are also available.

Goliya Instruments Pvt Ltd

Website: www.goliyainstruments.com

Radio communication analyser

The MT8821C radio communication analyser is designed for R&D of mobile devices/user equipment,



such as smartphones, tablets and M2M modules. It builds on the technologies of its popular predecessor, MT8820C, and supports all technologies, ranging from LTE-Advanced to 3G/2G, with its easy-to-use measurement functions for efficient radio frequency adjustment and testing in one unit.

Anritsu India Pvt Ltd

Website: www.anritsu.com

LEDs

LED streetlight

Pyrotech offers a complete range of energy-saving IP-66 certified LED super-mini streetlights with opti-