

mum thermal management and highly efficient constant-current driver, having short-circuit and open-circuit protection in die-cast aluminium housing. With these lights, you can save up to 80 per cent power. The power factor is >0.9 and the housing is weather-proof.

Pyrotech Electronics Pvt Ltd
Website: www.pyrotechlighting.co

SOFTWARE

PCB designer

Allegro PCB Designer Manufacturing Option from Cadence Design Systems is a comprehensive, powerful, easy-to-use toolset that makes it efficient and cost-effective for PCB designers to streamline the development of a release-to-manufacturing package for their products. It includes the Design for Manufacturing (DFM) Checker, Documentation Editor and Panel Editor modules.

Cadence Design Systems Inc.
Website: www.cadence.com

MCAD co-designer

Altium has released a new extension for its flagship PCB design tool, Altium Designer. MCAD Co-Designer: SOLIDWORKS helps to facilitate collaboration between mechanical and electronic design teams with integrated design data, a managed change environment for design revisions and lifecycle management for component creation, among other features.

Altium Ltd
Website: www.altium.com

MISCELLANEOUS

IoT edge node

Round Solutions has launched its wireless PingPong IoT edge node, a flexible and powerful hardware platform for connecting field devices to the cloud.

The PingPong hardware platform offers high-speed mobile modules for the IoT connectivity as well as numerous interfaces to the field,

which can also be controlled via the cloud.

Round Solutions GmbH & Co. KG
Website: www.roundsolutions.com

Fluxing and soldering system

The IS-T-300 from Manncorp is an all-in-one selective fluxing and soldering system, designed to de-



liver high quality and consistent, efficient performance. IS-T-300 comes fully-

equipped with advanced features like high-precision drop-jet fluxing, laser-controlled wave-height compensation and CAD data import.

Manncorp
Website: www.manncorp.com

Galvanic skin response system

Wearables developers can now evaluate galvanic skin response (GSR) sensing with MAXREFDES73# reference design from Maxim Integrated.

Its key advantages are:

- Fast time-to-market. Integrates DAC and ADC signal chain components, low-power MCU, external Bluetooth and Android apps and firmware components to quickly



develop and test designs

- High accuracy. 16-bit integrated analogue front-end (AFE)

- Low power consumption. Operates for one week on one battery charge

Maxim Integrated Products Inc.
Website: www.maximintegrated.com

VoIP-GSM gateway

Matrix SETU VG is a compact VoIP-GSM gateway with up to 4/8 GSM and 3G SIM support. Integrated GSM/3G connectivity and open-standard SIP support enables SETU VG gateway to easily connect with leading IP phone systems, software based IP-PBXs, hosted and SIP trunking services.

It also delivers value added features such as hot swapping of SIM cards, remote SIM balance inquiry and



recharge, automatic number translation, configurable call minutes, SMS notifications, monitoring and auto provisioning for mass deployments.

Matrix Comsec
Website: www.matrixtelesol.com

Ultra-HD monitor

The VP2780-4K offers an ultra-high 3840 × 2160 4K UHD resolution. The SuperClear IPS display technology provides consistent and true-to-life images from any viewing angle. It delivers the ultimate colour performance with 100 per cent sRGB colour coverage.

The VP2780-4K has 10-bit colour, 14-bit processing, 3D LUT and Delta E₂ colour accuracy, which renders the image on display and printout as accurately as it is on camera. Each display is individually calibrated and manually adjusted for greater colour accuracy as part of the production process to ensure perfect image quality.

ViewSonic Corp.
Website: www.viewsonic.com

Controller

Serving as a cost-effective alternative to a PLC, the controller provides 40



digital inputs along with 12 analogue inputs. There are a total of 30 relay outputs, along with two SSR outputs. Analogue output ports include two

PWM ports and two standard 4mA-20mA output ports. The controller unit comprises a digitally-calibrated 14.5cm (5.7-inch) TFT display.

Godrej & Boyce Mfg. Ltd
Website: www.godrej-ia.com