



STM8A

8-BIT STANDARD AND LOW POWER MICROCONTROLLERS FOR AUTOMOTIVE APPLICATIONS

- STM8 up to 24 MHz CPU
- 8 to 128 Kbytes of embedded Flash, up to 6 Kbytes of SRAM and up to 2 Kbytes of data EEPROM
- Packages up to 80 pins
- Supply voltage: 2.95 to 5.5 V for STM8AF, 1.65 to 3.6 V for STM8AL
- Up to four low-power modes: down to 1 μ A with complete context retention
- State-of-the-art digital and analog peripherals
- Up to 150 °C ambient temperature
- Qualified to AEC-Q100
- Certified CAN drivers
- Free certified LIN drivers
- Touch-sensing and LCD lines

Applications

- CAN controllers
- LIN nodes
- Actuators
- Sensors
- Safety microcontrollers
- Car radios
- Immobilizers
- DC motor control
- HVAC
- Remote keyless entry
- Tire pressure monitors
- Alarms
- BLDC electric motor control
- Sensors

STMicroelectronics Pvt Ltd
Plot No 1, Knowledge Park III,
Greater Noida 201308, Uttar Pradesh, India

Authorized distributors

• Arrow: Murali: +91-96866 79492 • Asia Lucky: Rekha: +91-98999 75331 • Avnet: Sravanthi: +91-99805 67572
• EDOM: Raghunatha. G: +91-81304 26926 • Future: Pawan: +91-98452 22703 • Teck: Sumit: +91-98997 35127
• Tomen: Priti: +91-98197 94974 • WT: Ramkumar. N: +91-90080 88998 • Yosun: Anurag: +91-99106 45646