

Fig. 9: After change

1. Controls and displays associated with each other should be placed in a compatible way

2. There should be a very clear demarcation between visual display elements and controls

3. Horizontal hand movements are better than vertical

4. Movement of hands towards the body is better than away from it

5. Horizontal orientation of keys is often preferred

6. Square keys are preferable as compared to other shapes

7. The maximum number of keys in a row should not be more than four




Fig. 10: Designing of a push button




Fig. 11: Designing of a membrane key

8. Most frequently used buttons should be on the right side of the system

Finally, let us see the engineering aspect of the UI. This essentially ensures that the UID is easily manufacturable and does not need a complex assembly process. This is also important from the product-service point of view.

Figs 10 and 11, respectively, show how a push button and a membrane key, both LCD UIs, can be designed for ease in manufacture.

These two designs are representative designs as engineering depends on the components and the manufacturing process used. Higher the automation, more the precision needed for the design. ●



**Good-Ark Semi USA
LAUNCHES NEW
PRODUCTS IN INDIA**



**MOSFET • DIODE • RECTIFIERS
• BRIDGE RECTIFIERS • PROTECTION DEVICE
• WAFER / BARE DIE • MEMS DIE**

**We do all types of
PCB Assembling
(Through Hole)**



**Seeking
new
sub-distributors
in India**

• ASSEMBLE THROUGH-HOLE PCB'S
• EXPERIENCED AND EFFICIENT
TECHNICAL TEAM
• WAVE SOLDERING

• COMPETITIVE
PRICE
• TIMELY DELIVERY
• GOOD FINISHING

For more information and product details, please contact our authorized distributor



JAC Electronics Private Limited
36/1267-A, 2nd Floor, Vaidyar Lane, Judges Avenue Kaloor, Cochin - 682017
Ph: +91 476 262 8969, +91 8111828889, +91 9946969969, +91 8111889652
Email: info@jacelectronics.com, Web: www.jacelectronics.com