

# STM32L0 Series

## Ultra-low-power MCUs Tailored to your needs



## Bringing Even More Efficiency to Power-Conscious Devices



- Based on ARM® Cortex®-M0+ Architecture
- 1.71 to 3.6 V VDD range
- 139  $\mu\text{A}/\text{MHz}$  (Run mode at 32 MHz)
- 76  $\mu\text{A}/\text{MHz}$  (Run-optimized)
- 340 nA Stop mode + Full RAM
- -40 to +125°C operating range



- USB 2.0 FS Certified
  - Crystal-less
  - Battery Charger Detection

- Ultra-low-power ADC
  - 12-/16-bit resolution down to 1.65 V



- Full Flash protection
- AES hardware encryption
- True random number generator
- Built-in error correction code
- Ultra-low-power time counter with 16-bit low-power timer
- Low-power UART for communication up to 9600 baud in Stop mode



- Adaptive inrush current



Get STM32L0 Innovation into your applications



Gas/water meter  
Industrial sensors  
Door lock



Fitness trackers  
Blood pressure  
Glucose meter



IoT/USB  
connected objects

Make the Switch from 8-Bit

New comer  
into STM32  
Portfolio  
TSSOP14



STMicroelectronics Pvt Ltd

Plot No 1, Knowledge Park III,  
Greater Noida 201308, Uttar Pradesh, India

Authorized distributors

• Arrow: Murali: +91-96866 79492 • Asia Lucky: Rekha: +91-98999 75331 • Avnet: Sravanthi: +91-99805 67572  
• EDOM: Raghunatha. G: +91-81304 26926 • Future: Pawan: +91-98452 22703 • Teck: Sumit: +91-98997 35127  
• Tomen: Priti: +91-98197 94974 • WT: Ramkumar. N: +91-90080 88998 • Yosun: Anurag: +91-99106 45646

Send Enquiry to: [mcu-enquiry@st.com](mailto:mcu-enquiry@st.com)

[www.st.com/stm32L0](http://www.st.com/stm32L0)