



FEEDBACK

YOUR SUGGESTIONS

AUDIO BUFFER

I have a query regarding 'High-Impedance Audio Buffer with JFET' DIY article published in February issue. Please clarify whether the circuit is for single channel or stereo.

Sreenivasa Kharideha

Through email

The author Petre Tzv Petrov replies:

The circuit published is designed for a single-channel audio system. If you want stereo input, you should use two similar circuits, one per channel. For quadro input, you should use four circuits, one per channel. You can use as many circuits as you wish with the same power supply to make a multi-channel buffer.

TECH FOCUS

In Tech Focus article titled 'High-Flying Solutions To Connect The World' published in January issue, on page 48, in first column, dynamic spectrum sharing (DSA) should be dynamic spectrum access (DSA).

Nirakara Mahanta

Odisha

The author Janani Gopalakrishnan Vikram replies:

In literature, both terms—dynamic spectrum sharing (DSS) and dynamic spectrum access (DSA)—are used for the same concept, almost synonymously.

HOME AUTOMATION

The 'Home Automation System' DIY article published in May 2015 issue is an awesome project. I am doing it as my final-year project but I need your help for connecting different electronic devices that could be controlled through this system.

Naveen Kumar

Through email

The author Kulbhushan Srivastava replies:

First, make multiple relay-interface modules and provide device IDs for all modules in the firmware during programming. The same device ID should match with the touch control panel.

Corrections

In 'Device for Charging Three 12V Batteries' DIY project published in January issue, on page 133, charging voltage for BATT.1 mentioned as $(15V-0.7V) \times 2=13.6V$ is wrong. It should be $(15V-0.7V) \times 2=28.6V$.

Pamarthi Kanakaraja

Assistant professor,
Usha Rama College of Engineering and Technology,
Andhra Pradesh

EFY. Thanks for pointing out. Actually, use of braces in the given equation is wrong. If J1 is opened and J2 is closed, charging voltage should be $15V-(0.7 \times 2)=15V-1.4V=13.6V$.

In 'Low-Cost LPG Leakage Detector' DIY article published in January issue, under Circuit and Working, Darlington transistor TIP122 (T2) should be TIP122 (T1).

Dinesh Kumar

Through email

EFY. Thanks!

In 'Why e-Waste Cannot be Taken Lightly' article published in January issue, on page 26, in the table titled 'Urban mine: An estimate of material value of e-waste in 2014', under Materials, gold is given symbol Ag (in periodic table), instead of Au.

Satyam N. Nambur

Hyderabad

EFY. Thanks for pointing out the mistake!

In 'Low-Cost Dusk-Down Controller' project published in January issue, switches S1 and S2 along with loads should be on drain side of T1. It is because as per datasheet, VGS should be 10V and threshold is up to 4V to fully turn on the MOSFET.

Shatrugit Soraisam

Through email

EFY. Thanks!

In 'Fingerprint Door Unlock System Using Arduino' DIY article published in January issue, position/orientation of the LCD connector in the PCB is wrong.

Pramod Kumar

EFY. Thank you for pointing out the mistake! However, we regret the inability to include under 'Spot an Error' category since the emails were received after the deadline.

In Jackson Hsu's interview, published in January issue, on page 104, ESR is wrongly expanded as erythrocyte sedimentation rate. In the context of capacitors, ESR stands for equivalent series resistance.

Deb Biswas

EFY. Thanks!

'Spot An Error' AWARD Winners

In First Look section, in 'Windows 10 phone from Microsoft,' published in January issue, battery rating is wrongly given as 3340mAh instead of 3000mAh.

Siddharth Kaul

In First Look section, in 'Lenovo Announces Idea Center Stick 300' published in January issue, contents are given for Nighthawk x8 AC5900.

Adil Khan

In 'Device For Charging Three 12V Batteries' DIY article published in January issue, one end of resistor R5 (3.3k) is floating in the PCB layout. It should be connected to the rectified output or positive terminal of capacitor C2.

A. Samiuddin

In 'Device for Charging Three 12V Batteries' DIY article published in January issue, on page 133, it is wrongly mentioned that when jumpers J1 and J2 are opened, charging voltage for battery (BATT.1) will be around $15V-0.7V=14.3V$. It should be 12.9V. If jumpers J1 and J2 are closed, charging voltage for battery BATT.1 will be 14.3V.

Parveen Kumar