

COMPONENTS

IGBT driver core

Power Integrations has launched its latest SCALE-2+ dual IGBT driver core, 2SC0435T2G1-17, which has a footprint of only 57.2x51.6mm and height of just 20mm.



The SCALE-2+ technology enables soft shut down (SSD) to be implemented in the event of a short circuit without requiring additional components. This is beneficial in applications with low stray inductance, where full advanced active clamping (AAC) may not be required.

If desired, the core can also provide full AAC. Designed to drive all standard 1200V and 1700V IGBTs, this driver core features an embedded paralleling capability to simplify inverter design at high power ratings.

Power Integrations

Email: peter.rogerson@power.com

MEMS chipset

Texas Instruments has announced the expansion of its near-infrared (NIR) chipset portfolio with fully-programmable micro-electro mechanical systems (MEMS) chipset that enables ultramobile analysis for a 700nm to 2500nm wavelength range.

The DLP chipset, consisting of



DLP2010NIR digital micro-mirror device (DMD), DLP2010 integrated power management and DLP2010 controller, boasts low power consumption, programmable high-speed patterns and the latest high-tilt 5.4µm pixel size for use in compact optical designs.

Texas Instruments

Website: www.ti.com

PCB terminal block

The new PCB terminal block, 830-A111-SMD, with the pitch of 3.5mm offers strong performance in the smallest space. The position of entries in parallel to the PCB enables housing with external connection. Due to small space requirement and white colour, it is suited to various applications in lighting industry.


The front of the terminal is equipped with pushers to be handled with standard screwdrivers for removal of parallel connected conductors.

Brilliant Electro-Systems Pvt Ltd

Website: www.brilliantelectronics.com

Power management IC

ROHM has announced a dedicated system power management integrated circuit (PMIC), BD2613GW, to sup-



port next-generation 14nm Intel Atom processor for tablet-PCs. A highly-integrated power management solution with industry's leading power efficiency, ROHM's PMIC is targeted towards ultra-thin form factor tablets.

ROHM Co. Ltd

Website: www.rohm.com

Thermal protector

This thermal protector is rated at 5A 250V AC (resistive), having cut-off temperature range from 50°C to 150°C.



It is commonly used in electric motors, battery charges, transformers, solenoids, heating pads and electric chimneys, among others.


ELMECH Industries

Email: info@elmi.in

Website: www.elmi.in

Connector

Phoenix Contact provides a variety of electronic housings that can be installed quickly and reliably on a common 35mm DIN rail. Apart from a few exceptions,



these connecting terminal blocks can be fitted and machine-soldered during PCB assembly.

Phoenix Contact India Pvt Ltd

Email: adverts@phoenixcontact.co.in

DCM converter module

Vicor Corp. has announced the expansion of its DCM converter module series of isolated, regulated DC-DC converters within Vicor's converter housed in-package (ChiP) power component platform. This series now covers critical applications in aerospace, EV/HEV, rugged systems, industrial and telecom/datacom.

These DCMs provide nominal input voltages of 24V, 28V, 48V, 270V, 290V and 300V, with nomi-