

nal outputs of 48V, 36V, 28V, 24V, 15V, 12V and 5V, and are available in packages with up to 600W of power.

Vicor Corp.

Website: www.vicorpower.com

TEST & MEASUREMENT

Digital light meter

MECO-G has introduced a handheld digital LUX meter with LCD display called R-LX 50B. This digital meter



has three ranges: 0-1999Lux, 2000-19,000Lux and 20,000-50,000Lux. It offers data-hold facility and operates on a single 9V battery.

Goliya Instruments Pvt Ltd

Email: sales@goliyainstruments.com

Website: www.goliyainstruments.com

Signal generator

Tektronix has introduced TSG4100A series of signal generators. These RF signal generators complement other leading mid-range RF test solutions from Tektronix, such as USB based RSA306 spectrum analyser, MDO4000B and MDO3000 mixed-domain oscilloscopes.

TSG4100A series includes three models with carrier frequencies from DC to 2GHz, 4GHz and 6GHz, respectively.

Instruments provide spur-free outputs with low phase noise (-113dBc/Hz at 1GHz), outstanding amplitude accuracy ($< \pm 0.4\text{dB}$ at 1GHz, 0dBm CW signal from $+16\text{dBm}$ to -100dBm level range) and excellent frequency resolution ($1\mu\text{Hz}$ at any frequency).

An oven-controlled crystal oscillator time-base provides $< \pm 0.002\text{ppm}$ temperature stability and $< \pm 0.05\text{ppm}$ aging stability.

Tektronix Inc.

Website: www.tektronix.com

Temperature sensor

The new resistance temperature detector's (RTD's) highly-integrated analogue front end (AFE) measures temperature while detecting overvoltage, shorts and open circuits. It consumes minimal power and provides better than $\pm 0.5^\circ\text{C}$ accuracy. The temperature appears immediately on an LED display for a quick and convenient snapshot of coarse temperature values.

For user convenience, it fits in a standard industrial form factor. For versatility, it supports all three IO-link speeds. The sensor is available for use with a 2-wire, 3-wire or



4-wire PT100 RTD over a wide temperature range.

Maxim Integrated

Website: www.maximintegrated.com

POWER SUPPLY

Hybrid battery

INPHYNT Bijli Ghar 160Ah model offers more than 315 minutes of RCA, that is, reserve capacity amperes, which decides the backup time of the battery. It weighs more than 37kg in dry conditions.



An innovative product, it has more than 600 lifecycles and takes one-third time to recharge if compared to tubular plates. Its excellent charge-retention quality also helps bring down the electricity bill.

INPHYNT Accumulators India Pvt Ltd

Website: www.inphynt.com

SOLAR

Solar connector

This solar connector provides high-class environmental protection as per




IP-68 standard. It finds applications in solar panel sub-assemblies, rooftop solar PV and utility-grade MW installations.

Elcom International Pvt Ltd

Website: www.elcom-in.com

MPPT charge controller

Stellar Innovations has launched MPPT based solar charge controllers, especially designed for use with thin film solar panels.



The unique feature of this product is that it can take PV input up to 150V DC from thin film panels. By using this MPPT device, you can save on solar system cost as thin film panels are available much cheaper.