

COMPONENTS

Chipsets

STMicroelectronics (ST) has announced its new HD HEVC Liege3 family of chipsets for entry-level set-top-box (STB) markets. These include satellite variants (STIH337/STIH332), cable-market products (STIH372) and IPTV STB devices (STIH307/STIH302).

The family combines the latest architectures used in ST's Cannes (STIH310/STIH312/318) products with optimised IPs to deliver future-proof systems on chips (SoCs) with high integration. This enables large-scale migration of entry STBs towards high-efficiency video coding (HEVC).

STMicroelectronics

Website: www.st.com

32-bit microcontrollers

Microchip has launched a new series within its high-performance PIC32MZ family of 32-bit microcontrollers.



These feature an integrated hardware floating point unit for high performance and lower latency in intensive single- and double-precision maths applications. Microchip also offers a 12-bit, 18MSPS analogue-to-digital converter for a wide array of high-speed, wide-bandwidth applications.

Microchip Technology Inc.


Website: www.microchip.com

Power delivery controller IC

ROHM has announced a new class of power receiver controller integrated circuits (ICs) compatible with the latest USB power delivery (Rev2.0) and

Type C (Rev1.1) standards.

The BM92TxxMWV series supports not only conventional USB power supply up to 7.5W, but the



newly-expanded power range as well up to 100W (20V/5A) for USB Type C connected devices. This makes it possible to drive equipment with larger power requirements such as TVs and PCs via USB and at the same time enable conventional USB-equipped portable devices (like smartphones and tablets) to be charged up to four times faster than the previous standard.

ROHM Co. Ltd

Website: www.rohm.com

Controller

ICL8105 from Infineon is a digitally-configurable flyback controller with power factor correction (PFC) for constant power LED drivers from 10W to 80W. The controller employs powerful algorithms and supports multiple operating modes.



Advantages are a high efficiency, PFC and low distortion. This produces a high quality of light with no flickering. The controller has an input of 0V to 10V dimming, eliminating the need for an oscillator including power supply. An active-burst mode significantly extends the dimming range, while preventing undesirable effects such as flickering or shimmering.

Infineon Technologies India Pvt Ltd

Website: www.infineon.com

System on chip

Renesas has announced R-Car W2R SoC, the first member of the new Renesas R-Car family of devices de-

veloped specifically for V2X applications. The new automotive wireless-communication SoC is designed for



vehicle-to-vehicle and vehicle-to-infrastructure communication in the 5.9GHz band.

Renesas Electronics Corp.

Website: www.renesas.com

Half-bridge gate driver

Texas Instruments has introduced a half-bridge gate driver for discrete power metal oxide semiconductor field effect transistors and insulated gate bipolar transistors (IGBTs) that



- Advanced noise tolerance
- -40°C to 125°C operating temperature
- 30% smaller footprint

TEXAS INSTRUMENTS

operate up to 600V. The UCC27714 high-side, low-side driver with 4A source and 4A sink-current capability reduces component footprint by 50 per cent, enabling higher power density in high-frequency, offline AC/DC power supplies used in server, telecom and industrial designs including uninterruptible power supplies.

Texas Instruments

Website: www.ti.com

Transceivers

ON Semiconductor has introduced three new KNX-certified twisted pair transceivers for smartbuilding applications. The devices allow small, low-cost external components, while delivering increased regulator current and boosting overall efficiency by up to 20 per cent compared to existing solutions.