

The NCN5110, NCN5121 and NCN5130 integrate two high-efficiency DC-DC converters and a 20V low drop-out regulator for powering external loads from the bus. The devices are offered in a QFN-40 package and are specified for operation over the extended temperature range of -40°C to 105°C.

ON Semiconductor

Website: [www.onsemi.com](http://www.onsemi.com)

## LLC controller

The FAN7688 incorporates Fairchild's innovative charge current control technology, which enables it to utilise current mode control, as opposed to voltage mode control. FAN7688 allows for tighter and faster output regulation against load transients and also simplifies the control loop, which enables designing it into power supplies.

Additionally, FAN7688's adaptive dual edge secondary side synchronous rectifier control ensures high reliability and stable SR operation of both load and line transients.

Fairchild

Website: [www.fairchild.com](http://www.fairchild.com)

## Stepper motor drive

MSD-05-EM is a bipolar micro stepping drive used for motion controlling and robotics. The drive is compact, rugged and the dual H bridge configuration makes it more reliable



in industrial applications. Large control signal operating voltage range makes the driver user friendly. It is facilitated with inbuilt short-circuit and overload protection. A 7-step drive current setting makes the drive easy to use with a wide range of stepper motors. The drive comes with a detachable connector terminal and can be easily mounted on the panel.

ELECTROMECH

Email: [emechdrives@gmail.com](mailto:emechdrives@gmail.com)

## Analogue ICs

Freescall's new two-wheel SB0400 IC is designed for use with motorcycles, while the single-wheel SB0401 IC is intended for scooters and lighter motorcycles. Both products are leadless and neither requires bulky heat-sinks, saving system cost and space.

Featuring Freescall's SMARTMOS analogue-mixed-signal technology, the devices integrate ABS system's wheel speed sensor interface, valve drivers, motor pump driver, safety switch and safety state machine into the smallest package size for motorcycle and/or scooter designs.

Freescall Semiconductor

Website: [www.freescall.com](http://www.freescall.com)

## Power supply modules

The new AAF-05 series from Minimax is a range of ultra-small, fully-encapsulated 5W AC-DC power supply modules designed for easy PCB mounting with solder pins.



The modules feature EMI filter to meet EN 55011/55022, class B and EN

55014 standards. EMC immunity complies with EN 61000-6-1. The low stand-by power consumption complies with European ErP Directive 2009/125/EC standard. Universal input voltage range of 84-264V AC and an international safety approval package qualifies these power modules for worldwide markets.

Minimax Technology Co Ltd

Website: [www.minimax.com](http://www.minimax.com)

## Firecracker reed sensor

Littelfuse has introduced the 59022 series firecracker reed sensor, which is a compact, cylindrical, magnetically-operated sensor capable of switching up to 265V AC/300V DC at 10W/VA.




Its diameter of just 5.8mm (0.228-inch) makes it easy to install into confined spaces in exist-

electronics  
FOR YOU

# Original, innovative circuit ideas are invited

from designers and  
experimenters  
for publication in EFY magazine



**Honorarium (minimum ₹1,000)  
will be paid to the contributors soon  
after publication of their articles.**

Complete details may be sent to the

'Editor, Electronics For You,  
D-87/1, Okhla Industrial Area Phase 1,  
New Delhi 110020'  
or emailed to [editsec@efy.in](mailto:editsec@efy.in)

For editorial guidelines, visit  
[http://efymag.com/Guidelines\\_for\\_EFY\\_authors.doc](http://efymag.com/Guidelines_for_EFY_authors.doc)