

Aplab Introduces

Advanced Version of Digitally Programmable High Power DC Power Sources

APLAB has replaced its widely popular VSP Series of Ultra Compact, High Efficiency Programmable DC Sources with an advanced version that gives higher power, higher regulation, higher efficiency and more programming options. The new series is designed aiming for even larger sale in Europe and USA besides the Middle East, Far East and India.

HI-POWER PROGRAMMABLE DC POWER SUPPLIES - PHP Series 800W to 8000W DC Output



Features

- High Power Density: 1400W in a 1U High Euro Rack unit
- Soft Switching for low losses and low Ripple and Noise
- Industrial Digital Encoder for Voltage and Current Setting
- μ P based system for data Logging and ultra-stable voltage reference
- Active Input PFC with universal Line Input: 95V to 270V AC/ 50-60Hz (single ph)
- Red and Green 3 Digit Bright LED Display for output Voltage and Load Current
- Isolated Analog Programming and Monitoring Surface
- Wide Choice of Interface RS232, RS485, GPIB for External Programming
- Optional Ethernet Interface Card-kit

Available Models

800W	1400W	2800W	4200W	8000W
0-10V/0-80A	---	---	---	---
0-20V/0-40A	0-20V/0-70A	0-20V/0-130A	0-20V/0-210A	0-20V/0-360A
0-30V/0-2A	0-30V/0-47A	0-30V/0-87A	0-30V/0-140A	0-30V/0-240A
0-40V/0-19A	0-40V/0-35A	0-40V/0-65A	0-40V/0-105A	0-40V/0-180A
0-60V/0-12.5A	0-60V/0-24A	0-60V/0-44A	0-60V/0-72A	0-60V/0-120A
0-80V/0-9.5A	0-80V/0-17.5A	0-80V/0-34A	0-80V/0-53A	0-80V/0-90A
0-120V/0-6.5A	0-120V/0-12A	0-120V/0-22A	0-120V/0-36A	0-120V/0-60A
1U	1U	2U	3U	6U