



FEEDBACK

How Things Work

I am addicted to *EFY* magazine! Thank you for cherishing us for the last 40 years! I request you to add How Things Work section to the magazine. The topics can range from daily-use electronic devices to telecommunications. It would be a joy to read such articles.

Ismail Taibani
Through email

RC Boat Modelling

I want to purchase the kit mentioned in 'Basic Guide to Radio-Controlled Boat Modelling' DIY article published in August issue. Is it available online?

Dr R.S. Gad
Department of Electronics
Goa University, Goa

The author T.K. Hareendran replies:
Here are some links where you can purchase radio-controlled boat kits and their spare parts:

www.rcbazaar.com/category.aspx?categoryid=259
www.rcracinghobbies.com/boats.html
www.thehobbyshop.in

Low-Cost 6-Bit DAC

Let me know if there is a way to modify the 'Low-Cost 6-Bit DAC' circuit published in January issue for a 4-bit or a 16-bit DAC.

Sreeram P.R.
Through email

The author Petre Petrov replies:

You can easily reduce the number of the bits as explained below:

Let us say, $LSB = \text{bit } D0$, $MSB = \text{bit } D7$

Remove the $LSB (D0)$ and you get a 7-bit DAC; remove the $LSB (D0)$ and $D1$, you get a 6-bit DAC; remove $D0$, $D1$ and $D2$ and you get a 5-bit DAC; remove $D0$, $D1$, $D2$ and $D3$, you get a 4-bit DAC and so on.

From Facebook: EFY's Electronics Design Community

I am very excited that my colleague Kaustubh is giving a talk on 'Build a SmartHome Using Renewable Energy Micro-Grid with Existing Infrastructure' at this year's eRocks.

Kaustubh came to know about FluxGen's work in renewable energy systems through an article in *Electronics For You* on solar energy systems. He applied for the position of intern at FluxGen after reading that article as he was very keen on working in solar domain. And now, as chief engineer of FluxGen, he will be representing us and showcasing our work at the conference hosted by EFY!

Ganesh Shankar

☐ Wooh... This post takes me about two years back. When I Googled "employment in solar," I happened to go through an article in *Electronics For You*. Certainly, this article helped me become a part of the most enthusiastic engineers I have ever met in my life.

Kaustubh Karnataki

☐ I am working on an Internet of Things (IoT) project using Intel Edison. I wish to publish it in *EFY* magazine.

Rushiraj Jawale

EFY. Please send complete details of the project to editsec@efy.in

For editorial guidelines, you may refer to efymag.com/Guidelines_for_EFY_authors.doc

You can also increase the number of bits, but that is a bit more complicated. If you need more than an 8-bit DAC, I suggest you use monolithic DACs. Perhaps, we could address that in a separate article.

Thermocouple Tutorial

I found some mistakes in 'Thermocouple Tutorial with Arduino Interfacing' DIY project published in September issue. Those are listed below:

1. Transformer (X1) rating is given as 9V-0-9V in the PCB layout but 12V-0-12V in Parts List.

2. CON2, CON3 and CON4 are not included in Parts List. CON2 pin pitch should be mentioned as it is different from other connectors.

3. It is mentioned ATmega32 with Arduino UNO but it should be ATmega32P.

4. On page 120, you have explained about Arduino UNO board with 13 digital pins instead of 14 digital pins.

5. Arduino UNO board power supply should be provided by a USB port or Vin (9V-12V). In this circuit, Arduino UNO is being powered by 7805, which is wrong. It will short

'Spot An Error' Award Winner

In 'Lift Indications' DIY article published in September issue, the symbol for VR1 is wrong. It should be preset symbol. Reset pins of IC2 and IC3 should have active low signs, with a bar on each reset pin.

Vijay Kakul

with Arduino UNO's own 5V regulator.

Gunjan Maheshwari
Through email

The author Ronie Adhiraaj Ghosh replies:

1. PCB layout was designed by EFY Lab. However, any transformer with 9V to 12V will work.

2. Connectors are for modularity and different designers may choose to construct differently. That is the ease of working on Arduino.

3. Arduino UNO used in the project was based on ATmega328, not ATmega32P.

4. It should be 14 digital pins. It is a slip of pen.

5. USB supply is not used in this project. In my board I have used an external 7805. Like mentioned earlier, different people use different designs.