

against ESD as high as 30kV and is suitable for high voltage applications up to 32V DC.

Littelfuse Inc.

Website: www.littelfuse.com

Server memory chipset

Rambus has introduced R+ DDR4 server memory chipset, RB26, for RDIMMs and LRDIMMs, delivering superior performance and capacity for both enterprise and data centre server markets. The first in a family of R+ chips, RB26 is an enhanced, JEDEC-compliant memory module chipset designed to accelerate data-intensive applications, including real-time analytics, virtualisation and in-memory computing, with increased speed, reliability and power efficiency.

Rambus Inc.

Website: www.rambus.com

Diodes

Vishay Intertechnology has launched two new SurfLight high-speed infrared (IR) emitting diodes in compact 3.2mm × 1.6mm × 1.1mm surface-mount, top-view packages.

The new Vishay SurfLight IR emitting diodes are based on Vishay's GaAlAs surface emitter chip technology. The 850nm VSMY12850 and 940nm VSMY12940 semiconductors combine high radiant intensity and optical power with fast switching times.

Vishay Intertechnology Inc.

Website: www.vishay.com

TEST & MEASUREMENT

Contact resistance meter

The new contact resistance meter (model PCRM-200S) is a digital micro-ohmmeter, specially designed to measure extremely low resistances in micro-ohm. It is based on Kelvin 4-wire connection method



for measurement of low resistance. Selectable test current are 100A DC and 200A DC. Test information like current injected with measured resistance and voltage drop is displayed with real-time data on a LCD screen with backlight.

The Motwane Mfg. Co. Pvt Ltd

Website: www.motwane.com

Thermal imagers

The U5856A and U5857A can perform temperature measurements up to 650°C and 1200°C, respectively. This allows users to detect a wide temperature range for various applications such as petrochemical and steel processing, electrical and mechanical applications, building maintenance and even electronics applications.

Keysight Technologies Inc.

Website: www.keysight.com

Oscilloscopes

SIGLENT Technologies announces the official release of SDS1000X series super phosphor oscilloscopes.



The new SDS1000X series based on SPO technology is available in two bandwidths, 100MHz and 200MHz, a sample rate of 1GSa/s and a standard record length of 14Mpts.

SIGLENT Technologies

Website: www.siglent.com

Logic analyser

Logic16 is a logic analyser used to record, view, and measure digital signals. It currently has 17 different pro-



tol analyzers including serial, I2C, SPI, CAN and many more. Logic16 can sample two channels at 100MHz, four channels at 50MHz, eight channels at 25MHz or all 16 channels at 12.5MHz and can record up to 10 billion samples.

Uchi Embedded Solutions

Website: www.uchiembedded.co.in

Gas detector controller

Honeywell has launched a new wall-mounted controller called Touch-point Plus. It supports up to eight



channels of gas detection for industrial and light industrial sectors, making it easier for

operators to monitor the safety of their sites and staff.

Honeywell

Website: www.honeywell.com

LEDs

CoolLED driver

Harvard Engineering PLC has added ZigBee wireless control to its range of lighting power supplies. The 33W driver, called CLZ and part of the firm's



CoolLED range, offers dimming down to one per cent and includes a 2.4GHz radio—either built-in or remote.

Radio communication allows the driver to tap into Harvard's EyeNut monitoring and management system for indoor lighting.

Harvard Engineering PLC

Website: www.harvardeng.com

Xlamp LEDs

Cree has unveiled the new Xlamp XHP35 family of LEDs with 50 per cent more light output than