

Fig. 6: Component layout of the PCB shown in Fig. 5




Fig. 7: Configuration bit

of the resistors, capacitors and inductor to get proper output.

Software

The program is written in C language and compiled

Petre Tzv Petrov was a researcher and assistant professor at Technical University of Sofia (Bulgaria) and an expert-lecturer in OPPT (Casablanca), Kingdom of Morocco. Now, he is working as an electronics engineer in the private sector in Bulgaria



EFY Note

The source code of this project is included in this month's EFY DVD and is also available for free download at source.efymag.com website.

using HI-TECH compiler along with MPLABIDE to generate the hex code. The generated hex code is burnt into the MCU using a suitable programmer with configuration bit setting. The set configuration bit is shown in Fig. 7. The program is well-commented and easy to understand. Delay function is used to generate frequency. ●

www.pcbpower.com



PCB[®]
Power

What is New?



Flexible, RF PCB & PCB Stencil



Design solutions
PCB Design services & Design Software



Soldering Equipments

for small quantity SMD-PCB assembly

- ✓ Students
- ✓ Hobbyists
- ✓ Designers
- ✓ Automotive
- ✓ Industrial
- ✓ R & D
- ✓ Railway
- ✓ Telecom
- ✓ Space

New Inspiring Prices

Online PCB Specialist

- PCB Up to 24 layers
- High Frequency (RF) PCB
- Flexible PCB
- No Minimum Order Value
- Minimum Order Quantity : 1
- No Tooling Charges
- Delivery 24hrs onwards
- Online Quotes & Tracking
- 24Hrs. Online Assistance
- SMS Update services

Call us @ 7600012414 & 7600012415
E-mail - sales@pcbpower.com



Circuit Systems India Ltd.
B-24, GIDC, Electronics Estate, Sector-25,
Gandhinagar-382044, Gujarat, India