



Martin's Electronic Devices & Instruments
Research & Development in Electronics Since 1987

Technical know-how of Transformerless Solar Pump control up to 5HP

Features

- Suitable for standard 415V 3-Phase 0.25HP to 5HP pump
 - Panel input voltage range - 90V to 850V
 - AC Output voltage: 0 to 480V phase to phase, 0 to 65Hz.
 - Protections against dry-run, overload, short circuit and high volt.
 - MPPT VF drive will give maximum torque even at minimum sunlight
 - IGBT module directly mounted on heatsink
- 
- The system runs at maximum efficiency at all the time by constantly maintaining the motor in the right slip.
 - Wireless Zigbee connectivity to the PC/ Data logger. Internet uploading and online monitoring of panel voltage, current, power, energy produced
 - Material cost of 5HP Solar Pump Control is less than Rs. 15,000/- • Technical know-how cost is Rs. 12 lacs

3KVA to 30KVA MPPT with interleaved switching technology



Features

- Panel input 90V to 850V
 - IGBT module power stage.
 - Switching frequency - 20KHz per phase Resultant switching frequency of four phase interleaved switching - 80KHz
 - Maximum buck from panel VOC 440V to 80V battery
 - CCCV four-level battery charger with temperature compensation and MCCV to the load
 - Temperature compensated charging -22mV to -30mV per Deg C per battery (settable).
- Internal monitoring and recording of data like panel current, panel voltage, battery current, battery voltage is done using RTC and flash memory with year, month, date, day, hour, minute with leap year correction.
 - Four line LCD will display panel current, panel voltage, panel power in Watt, battery voltage, battery charging current, total output current (load current + battery current), total energy used in KWH, excess panel voltage, excess panel current, excess load current, excess temperature, short circuit trip.
 - Panel input high voltage protection, lightning surge at panel input protection, accidental high current panel connection protection, battery full charge cut off provided.
 - Material cost of 30KVA MPPT solar charger is approx. Rs.25000
 - Technical know-how cost is Rs.8 lacs.

Call : 092123 87080, 0484-2356429, 09400151111, 09400145111. Web: www.medielectronics.com
bangalore@medielectronics.net, cochin@medielectronics.net