



FEEDBACK

Article on Robotic Submarine

Please publish some articles on underwater submarine seabed surface using robots. I hope Efy is aware of the loss of our Indian coast guard, Dornier CG-791, near Tamil Nadu sea coast.

Prakash Raamaseshan
Ministry of Home Affairs
Government of India.

EFY: Thanks for the feedback! We will try to carry something on the mentioned subject if a suitable article is received from our contributors.

Solar Based Article

It would be helpful if you could start a series on solar panels and batteries required in solar cars or cycles. There are rumours on the Internet about solar power generation using static charges on Earth. Please help clear such myths.

John Tarun,
Through email

EFY: Thanks for writing to us and sharing your thoughts. Regarding the myths related to solar power generation using static charge of Earth, allow us to review the same. We do keep publishing articles related to the latest in solar technologies in *Electronics For You*. We will try and publish more.

IoT Course

I just completed my B.Tech and would like to learn and make IoT devices. Let me know if you have any training centre or workshop that provides training on the same.

Saurabh Jha
Through email

EFY: We have training centres in various parts of India for short-term courses on subjects such as Basics of Electronics, PCB design, PIC microcontrollers, VLSI design, Raspberry Pi, Arduino and Robotics.

Soon, we will be starting a training course on Internet of Things

'Spot An Error' Award Winners

In Design section, in 'Basic User Interface Design for Electronics Engineers' article of July issue, in Fig. 5, the resistance (minimum) and key width (maximum) are wrong. It should be force (minimum) and force (maximum) because Newton (N) is the unit of force.

Ramakanta Mohanta

□ In 'Arduino Based Gesture-Controlled Robot' DIY article published in July issue, a 16×2 LCD is mentioned in Parts List by mistake.

Ishan Shah

□ 1. In 'Electronic Door Lock Using Arduino' article, columns C1, C2, C3 and C4 are mentioned as capacitors and rows R1, R2, R3 and R4 as resistors.

2. In 'Low-Frequency Electronic Muscle Stimulator' circuit in July issue, ratings for transformers X1 and X2 are wrong. Current ratings should be less than 100mA for X2.

Vijay Kakul

Errata

In the Buyers' Guide on 'Pocket-Friendly Oscilloscopes under ₹ 50,000' in July issue, the price of Tektronix TBS1022 is wrongly listed as ₹ 39,555. The price of the product is ₹ 21,865.

(IoT) and some other subjects as well. For details please log on to www.efytechcenter.com

Wireless Gesture-Controlled Robot

I am using GY-61 ADXL335 accelerometer sensor in 'Wireless Gesture-Controlled Robot' DIY article published in January issue. Will the code given in the article work with this sensor?

Shripal Jain
Through email

□ I am using Arduino UNO in the mentioned project. How can I make the robot work?

Raj R.
Through email

The author Aquib Javed Khan replies: Mr Jain should not forget to connect AREF pin with 3.3 volt. He should check the code and the respective connections. He may download the source code from source.efymag.com.

It is simple to work with Arduino UNO board. One needs to just upload the code on Arduino, connect the circuit as shown in the article. Note that pins 16, 17, 18 and 19 may have

different functions and values on Arduino board. For example, pins 16, 17, 18 and 19 of ATmega328 are digital pins 10, 11, 12 and 13, respectively, on Arduino board.

Ultrasonic Radar

Please provide more details on the ultrasonic sensor used in 'Ultrasonic Radar Model Using Microcontroller ATmega128' DIY article published in February issue.

You have mentioned that the UDM sensor module has four pins but this module has only three pins for connection to the external circuit. Is there a readymade sensor available in the market?

Manu Shankar
Through email

The author Ashutosh M. Bhatt replies: A normal ultrasonic sensor has four pins, namely, Vcc, Gnd, Trig and Echo. In the given sensor, it is required to scan for received echo signal first; the distance is then calculated through the program.

There are three different types of ultrasonic sensors based on their output: normal, PWM and direct serial data. In this project, I have used the third one. It has three pins, namely, Vcc, Gnd and Serial data out, for interfacing. It is a smart 3-pin ultrasonic sensor.

EFY: A readymade 3-pin sensor is available; check at www.sunrom.com/c/distance-ultrasonic