


10W & 20W, 1x1" Package DC/DC Converters



↓ 50% Smaller

Power – 10W(MJWI10 Series), 20W(MJWI20 Series)

Isolation – 1.5KVDC

Ultra Wide Input Range – 4:1

Input Voltage – 24V, 48V

Output Voltage – 3.3V, 5V, 5.1V, 12V, 15V
±5V, ±12V, ±15VDC

- ✓ Efficiency up to 90%
- ✓ Remote On/Off Control
- ✓ Output Trim
- ✓ Complies with EN55022 Class A

Application

- Data communication equipments
- Mobile battery driven equipments
- Mixed analog/digital subsystems
- Industrial robot systems



Full Product Line



1-10W SIP Package

- Package: SIP-4, SIP-7, SIP-8, SIP-9
- Isolation Voltage: 1k, 3k, 6kVDC
- Efficiency up to 89%
- Operating Temperature -40°C to +85°C
- MTBF 2 Million Hours Minimum



1-6W SMT Package

- Package: SMT-8/10, SMT-16, SMT-24
- Isolation Voltage: 1k, 1.5k, 3kVDC, 4kVAC
- Efficiency up to 85%
- Operating Temperature -40°C to +71°C
- MTBF 2 Million Hours Minimum
- Safety Approval



1-10W DIP Package

- Package: DIP-8, DIP-16, DIP-24
- Isolation Voltage: 1.5k, 3kVDC, 4kVAC
- Efficiency up to 86%
- Operating Temperature -40°C to +71°C
- MTBF 1 Million Hours Minimum
- Safety Approval



10-30W, 2"x1" Package

- Isolation Voltage: 1.5kVDC
- Efficiency up to 89%
- Operating Temperature -40°C to +71°C
- MTBF 1 Million Hours Minimum
- Safety Approval



20-30W, 2"x1.6" Package

- Isolation Voltage: 1.5kVDC
- Efficiency up to 89%
- Operating Temperature -40°C to +71°C
- MTBF 1 Million Hours Minimum
- Safety Approval



7-60W AC/DC Power Module

- Package: PCB & Chassis
- Universal Input Range
- Isolation Voltage: 3kVAC
- Efficiency up to 84%
- Operating Temperature -25°C to +71°C
- Safety Approval



Minimax Technology Co., Ltd.
www.minimax.com.tw

India-Distributor:
Unified Electro-Tech Ltd.
E-mail: anand@unified.co.in

Tel: (+91) 80-26706677
www.unified.co.in