

in three sizes (7.2×7.2 cm², 9.6×9.6 cm² and 14.4×14.4 cm²) and operates off 110/230/440V AC.

Goliya Electricals Pvt Ltd, Mumbai

Fax: (022) 24168498

Phone: 24120456, 24133206

E-mail: geplmumbai@mtl.net.in,

goliya@bom5.vsnl.net.in

Web: www.goliya.com

Curve tracers

Iwatsu has launched a new series of curve tracers that support high voltages and large currents.

These state-of-the-art devices can be used to measure the characteristics of a range of discrete semiconductor



devices, from advanced high-voltage, large-current power devices such as IGBTs and power MOSFETs to more simple devices such as transistors, diodes and LEDs.

All models have collector supply modes (AC, full-wave rectification, DC and leakage current), and can support peak voltage of up to 3000V and peak current of up to 1000A.

USB ports and a LAN interface are provided as standard features, so measurement results can be saved in an external storage device, sent to a computer or compiled in a report.

Varsatech Instruments Co., Thane

Fax: (022) 25366115

Phone: 25433912

E-mail: varsatech@rediffmail.com

Insulation resistance tester

The IM561C insulation resistance tester from EQ Supplies is powered by 1.5V



AA-size alkaline battery and can measure resistance from 0.5 MΩ up to 1000 GΩ. It can be connected to a computer via USB cable, hence mak-

ing analysis of data easier.

The tester is capable of giving over-range and high-voltage warning. It measures 20.2×15.5×9.4 cm³ and comes with an extra rugged integral carrying case.

SUMITRON Exports Pvt Ltd, New Delhi

Fax: (011) 41410494, 25891761

Phone: 41410631-35

E-mail: sumitron@vsnl.com,

sumitron@airtelmail.in

Web: www.sumitron.com

TOOLS & EQUIPMENT

Development board for 16-bit microcontrollers and DSCs

Many engineers, educators, students and hobbyists need a low-cost solution for working with and debugging code on 16-bit microcontrollers and digital signal controllers (DSCs). Microchip



Technology Inc. has launched a complete, low-cost solution for designing with Microchip's 16-bit PIC24H microcontrollers and dsPIC33F DSCs, in a compact 2×7.6cm² footprint. The Microstick offers an integrated USB programmer/debugger that shortens learning curves. For maximum flexibility, it can be used standalone or plugged into a prototyping board. Educators are eligible for a 25 per cent discount on the product.

The Microstick is populated with a socketed microcontroller that can be easily swapped out.

Microchip Technology, New Delhi

Fax: (011) 51608632

Phone: 51608631

Web: www.microchip.com

COMPONENTS

8-bit microcontrollers for motor control

Fujitsu Microelectronics Asia Pte Ltd (FMAL) has introduced 8-bit microcontrollers with embedded flash memory

for such applications as microwave ovens, food processors, hair dryers and office equipment that require brushless DC motor controllers.

The new microcontrollers have a memory capacity of up to 60 kB and 48-pin packaging. Equipped with up to twelve channels of high-precision ADCs, chips in this series can receive multiple sensor inputs and run complex processing programs. The series includes various timer and communication functions that are useful for general-purpose applications, along with high-precision oscillators, thereby significantly contributing to reduction in the number of parts used in system architectures.

Fujitsu Microelectronics Asia Pte Ltd

Bengaluru Liaison Office, Bengaluru

Fax: (080) 28416660

Phone: 28419990

Single-phase DC-DC controller

Linear Technology has introduced a single-phase synchronous step-down DC-DC controller (LTC3816) implementing the Intel IMVP-6, IMVP-6+ and IMVP-6.5 protocols.

Intel mobile voltage positioning (IMVP) is a smart voltage-regulation technology that effectively reduces the amount of output capacitance required for a given output error budget.

On-chip support is provided for all the IMVP-6/6+/6.5 requirements, including a 7-bit VID code, start-up to a preset boot voltage, differential remote output-voltage sensing, programmable active-voltage positioning, output-current reporting (IMON, IMVP-6.5) and power optimisation during deep-sleep state to increase the battery run time.

The LTC3816 incorporates a parallel-input, 7-bit digital-to-analogue converter (DAC), which dynamically adjusts its output to the Intel CPU core supply voltage from 0V to 1.500V in 12.5mV steps. It can operate in pulse-skipping or forced continuous mode.

Arrow Electronics India Ltd, Bengaluru

Fax: (080) 51127784

Phone: 51353800