

eXtreme Low Power MCUs Maximize Battery Life

PIC® MCUs with nanoWatt XLP

Microcontrollers

Digital Signal
Controllers

Analog

Memory



Extend the battery life in your application using PIC MCUs with nanoWatt XLP Technology and get the industry's lowest currents for Active and Sleep modes.

- Low Sleep Currents with Flexible Wake-up Sources
 - Sleep current down to 20 nA
 - Brown-out Reset down to 45 nA
 - Real Time Clock down to 500 nA
- Low Dynamic Currents
 - As low as 45 μ A/MHz
 - Power efficient execution
- Battery Friendly Features
 - Enable battery lifetime > 20 years
 - Operates down to 1.8V with self write and analog functions
 - Low-power supervisors for safe operation (BOR, WDT)
- Flexible Peripheral Set
 - Integrated USB, LCD, RTC & touch sensing
 - Eliminates costly external components

GET THE MOST FROM YOUR BATTERY IN YOUR NEXT DESIGN!

- Visit www.microchip.com/XLP
- View the Low Power Comparison videos
- Download the Low Power Tips 'n Tricks
- Attend the new XLP class at a Microchip Regional Training Center



Get started with your low power design today using the XLP 16-bit Development Board (DM240311)

India Sales Office:

Bangalore (080) 3090-4444 • **New Delhi** (011) 4160-8631 • **Pune** (020) 2566-1512 • Email: asia.inquiry@microchip.com

www.microchip.com/XLP

