



Power Up Your LEDs


RGB LED Driver Series For LED Architectural Lighting

Two-Wire, Long Distance Transmission (2 Meters between 2 Clusters)

- Simple** Two-wire transmission protocol to support 1024 RGB clusters
- Smart** A-Token (Addressing Token) topology with self-alignment addressing
- Flexible** Achieve 65,536 gray scales at 10-bit data bandwidth
- Reliable** Phase-inversed CLK to assure signal integrity after long distance transmission

Part No.	Channel	Output Current	Sustaining Voltage	Supply Voltage	S-PWM	Built-In LDO	Signal Integrity	Transmission Interface	RoHS Package
MB16020	3	5-50mA	17V	3-5.5V	16 bits	---	Phase Inversed Output CLK	2 wires	SSOP16 / QFN3*3
MB16024	12						CLK Regeneration	2 wires	SSOP16 / QFN4*4
MB16030	3	5-150mA	40V	5V, 7-30V	16 bits	V		2 wires	SSOP16 / QFN4*4

A-Token Topology




If you are interested in our products, please leave your contact information and tell us where you see our advertisement, email to: marketing@mblock.com.tw, we'll provide free gifts to the first 20 inquiries.

Tel: +886-3-579-0068 • Fax: +886-3-579-8934 • Website: www.mblock.com.tw • Email: marketing@mblock.com.tw

CUT COST & SIZE

WITHOUT COMPROMISING ON QUALITY



Make your Panels Small & Save

TAPMAN®

www.microsmartindia.com



Rs.555/-

OEM's / Machine Manufacturers please contact with complete details to:
logic_devices@yahoo.com microsmart_systems@yahoo.co.in

Ph : 92461 60928, 98490 40928, Fax: 040-6554 5667

LIMITED PERIOD OFFER : BUY SAMPLES AT BULK PRICE
The Next Generation
Temperature Controller