

fleet management, mapping and robotics. It can support up to 51 channels.
Rhydo Technologies (P) Ltd, Cochin
Fax: (0484) 2370575
Phone: 2370576/9
E-mail: info@rhydolabz.com
Web: www.rhydolabz.com

TEST & MEASUREMENT

Wide-range laser particle-size analyser

Battersize has launched a laser particle-size analyser (Model 2000) with a range of 0.02 to 2000 microns for testing powders. The analyser features a 3-D automatic focusing system controlled by computer, fully automated one-click operation, automatic



concentration adjustment (when concentration is high it auto-dilutes, and when concentration is low it prompts for sample addition to optimise concentration) and free validation documentation.

The analyser can be used for pharmaceuticals, cement, titanium powder, talc, clays, soil, pesticides, battery material, graphite, petrochemicals, metallic powders, catalysts, mica, abrasives and ceramics.

MeasureTest Corporation, Mumbai
Phone: (022) 22027982
E-mail: sheesh@mtl.net.in

TOOLS & EQUIPMENT

Motor-driver evaluation platform

Texas Instruments has introduced a scalable evaluation platform for spinning motors. The DRV8412 evaluation kit (DRV8412-C2-KIT) includes all of the hardware and software needed to spin two brushed DC motors or a single stepper motor out of the box.

This highly integrated solution speeds up development of brushed DC and stepper motors running up to 6A continuous/12A peak at 50V. Applications include medical pumps, gate openers, stage lighting, textile manufacturing tools, and industrial or consumer robotics.

Texas Instruments (India) Pvt Ltd, Bengaluru
Fax: (080) 25048286
Phone: 25099221
Web: www.ti.com

COMPONENTS

High-current inductor in 6767 case size

Vishay Intertechnology has launched a new low-profile, high-current inductor in the 6767 case size. Featuring an ultra-low 4.0mm profile, the IHLP-6767DZ-11 offers high efficiency with maximum DCR down to 2.05 mΩ and a wide range of standard inductance values from 1.0 μH through 47.0 μH.

With a frequency range up to 750 kHz, the new inductor serves as a high-performing, space- and power-saving solution for voltage regulator module and DC-DC applications in end products including next-generation mobile devices; notebooks, desktop computers, servers, graphic cards, personal navigation systems, personal multimedia devices and automotive systems; low-profile, high-current power supplies and point-of-load converters; distributed power systems; and field-programmable gate arrays.

Vishay Components India Pvt Ltd, Bengaluru
Fax: (080) 25584291
Phone: 25586277
E-mail: business-asia@Vishay.com

Switching regulator

Linear Technology has introduced a 2.6A, 36V step-down switching regulator with dual linear controllers, in a 4x5mm² QFN or TSSOP-20E package. The LT3694 operates from 4V to 36V with transient protection to 70V, making it ideal for load dump and cold-crank conditions found in automotive

applications.

Its internal 3.5A switch can deliver up to 2.6A of continuous output current at voltages as low as 0.75V. Switching frequency is user-programmable from 250 kHz to 2.5 MHz, enabling the designers to optimise efficiency while avoiding critical noise-sensitive frequency bands. Each integrated LDO controller has an accurate programmable current limit up to 1A to provide an additional level of reliability.

Arrow Electronics India Ltd, Bengaluru
Fax: (080) 51127784
Phone: 51353800

Operational amplifier

Microchip Technology has launched the MCP6H01 and MCP6H02 (MCP6H01/2) operational amplifiers (op-amps). These op-amps have a bandwidth of 1.2 MHz and supply voltage from 3.5V to 16V.



The devices feature a low quiescent current of 135 microamperes (typ.), off-set voltage of 3.5 mV (max.), common-mode rejection ratio of 100 dB (typ.) and power-supply rejection ratio of 102 dB (typ.).

The MCP6H01/2 is targeted at applications that operate on voltages up to 16V, such as those in the medical (portable instrumentation, heart and blood pressure monitors), automotive (proximity, temperature or flow sensors) and industrial (high-side current sensing in power supplies) markets.

Microchip Technology (India) Pvt Ltd, New Delhi
Fax: (011) 51608632
Phone: 41608631
Web: www.microchip.com