

Power Packed Resistors From



WIRE WOUND RESISTORS

HSR/HSRC

Capacitor Discharge,
Wire Wound Symmetry Resistors
Power Rating : 8.25W & 11W (70°C)
Resistance Range : 10K to 70K
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features :
• Stainless steel mounting terminals
for direct mounting on to capacitors.

HSVA

Ceramic Encased With
Slots/Axial Type.
Power Rating : 4W to 17W (70°C)
Resistance Range : R04 to 82K
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features : • Low surface temperature.
• Pulse type available.

HCA

Power Axial Type
Power Rating : 1W to 20W (70°C)
Resistance Range : R10 to 56K
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features : • High insulation.
• Fire proof. • Resistant to
aggressive solvents.
• Pulse type available.
• PCB requirements.
• Bracket acts as heat sink.

HIA

Power Axial Type.
Power Rating : 0.5W to 20W
Resistance Range : R01 to 120K
Tolerances Available : 10%, 5%, 3%, 1%
Features : • Flame retardant
• Thermocouple precision power
• Pulse type available.
• Non-inductive type available.

CURRENT SENSE RESISTORS

OA / OP

Open Frame / Axial and
PCB Mounting - Shunt Type.
Power Rating : 0.5W to 5W (85°C)
Resistance Range : R002 to R10
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features : • Non insulated.
• Surge / current sensing applications.

OF

Open Frame
PCB Mounting -
Punched Out Style
Power Rating : 1W to 10W (85°C)
Resistance Range : R0002 to R068
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features : • Low TCR
• Tailor-made solutions possible

HEAL

Alloy Ribbon Element / Axial Type.
Square Profile Ceramic Tube.
Power Rating : 2.5W to 12W (70°C)
Resistance Range : R0025 to R20
Tolerances Available :
10%, 5%, 3%, 2%, 1%
Features : • Negligible inductance.
• Surge / current sensing applications.

OFSC

PCB Mounting.
Power Rating :
5W & 10W (70°C)
Resistance Range :
R00012 to R003
Tolerances Available :
5%, 3%, 2%, 1.5%, 1%
Features : • Silicone coated.
• Surge / current sensing applications.
• Negligible inductance.



**HI-TECH
RESISTORS
PVT. LTD.**

AN ISO/TS 16949:2002 CERTIFIED COMPANY

Buty Compound, Mount Road Extension, Nagpur-440 001, INDIA.
Tel : +91-712-2531134, 2533269, 2553691
Fax : +91-712-2528334, 2556351.
e-mail : info@htr-india.com | www.htr-india.com



SMD
ELECTRO COMPONENTS

FULL RANGE OF SMD ACTIVE
& PASSIVE COMPONENTS

Authorised Distributor



SMD E-Capacitors



SMD Transistors
SMD LED SMD Diodes
SMD Capacitors



SMD Resistors



CHIP TRANSISTORS / CHIP DIODES / CHIP LED'S / CHIP CAPACITORS / CHIP IC'S

- | | | |
|--------------------------------|--------------------------------------|----------------------------|
| • CHIP RESISTORS | • CHIP BRIDGE RECTIFIERS | • CHIP FERRITE BEADS |
| • CHIP RESISTOR NETWORKS | • CHIP TRANSIENT VOLTAGE SUPPRESSORS | • CHIP HALL SENSORS |
| • CHIP CAPACITORS | • CHIP IC'S | • CHIP IN LEADS & SENSORS |
| • CHIP TANTALUM CAPACITORS | • CHIP MOSFETS | • CHIP POTENTIOMETERS |
| • CHIP ELECTROLYTIC CAPACITORS | • CHIP REGULATORS | • CHIP FUSES |
| • CHIP ZENERS & DIODES | • CHIP OPTO COUPLERS | • CHIP SWITCH |
| • CHIP TRANSISTORS | • CHIP THERMISTORS | • CHIP MOV'S |
| • CHIP LED'S | • CHIP TRIMMER CAPACITORS | • CHIP SOLDER PASTE |
| • CHIP SCHOTTKY DIODES | • CHIP INDUCTORS | • CHIP SOLDER WIRE 26 SWG. |



54-C, Jyoti Estate, Proctor Road, Near Parijat bldg., Off. Lamington Road,
Mumbai - 400 007, INDIA. Tel : 91-22-3240 2444 • Mob : 93242 11912

E-mail : smdelectro@vsnl.net

STOCKIST OF ELECTRONIC COMPONENTS



Circuit Electro-Components Pvt. Ltd.



"Drug House", Bldg. 54-B, Proctor Road, Mumbai - 7, INDIA.
Pin Code : 400 007 • Tel : 2367 7777 / 2368 0888
Mob. : 93222 34370 / 93227 91112 • Fax : 91-22-2367 9335
E-mail : circuit@vsnl.com • Website : www.circuitelectro.com

