

Simplify Your Industrial Networking Connections for Renewable Power Automation



- Compact size and low power consumption
- Ring redundancy at the device level
- Rugged industrial design
 - ✓ UL508 certification
 - ✓ Full surge protection
 - ✓ Level 4 ESD
 - ✓ 2 kV isolation



Compact, Robust, and Flexible Network Solution for Solar Power Stations

Solar power stations include three major devices—a power inverter, a PLC, and meters—and require a reliable network for sending data to the backbone network and the control center. As solar farms are normally situated in open areas such as deserts, the devices used must be able to endure wide variations in temperature to provide reliable connectivity.

The NPort S8000 Series is designed to connect both serial and Ethernet devices, and ring redundancy is made possible through standard STP/RSTP or Moxa's proprietary Turbo Ring. With an all-in-one design, a variety of features, and the ability to work under extreme temperatures (-40 to 75°C), the NPort S8000 is the perfect choice for solar power station networking solutions. Choose the S8000 to optimize, simplify, and enhance your device networks.



NPort® S8000 Series

5-port Managed Ethernet Switch and 4-port RS-232/422/485 Device Server

- Rugged industrial design (UL508, full surge protection, Level 4 ESD, 2 kV of isolation on each serial port)
- Serial QoS for configuring serial data transmission priority
- Adjustable pull high/low resistor for RS-485 communications
- Ethernet redundancy with Turbo Ring (recovery time < 20 ms) or RSTP/STP supported
- Wide operating temperature from -40 to 75°C



DYNALOG
(INDIA) LIMITED

Dynalog (India) Limited
Kailash Vaidhyan, Parkside, Vikhroli (West), Mumbai - 400 079.
Tel: +91 - 22 - 4233 0000 | Fax: +91 - 22 - 2518 1930/40
www.dynalogindia.com | sales@dynalogindia.com
Ahmedabad | Bangalore | Dehradun | Mumbai | Pune | New Delhi

MOXA
www.moxa.com
india@moxa.com