

assessment. Life-cycle idea is the foundation for Siemens Enterprise Communications' environmental activities;



its objective is to determine and evaluate the environmental aspects and possible environmental effects with regard to the entire lifecycle of the company's products, from development through production, procurement, sales, services, use and recovery.

OpenStage phones too follow the standby initiative of European Commission with code-of-conduct compliance for power supplies and broadband equipment. And with optimised embedded hardware platform, these are capable of reducing the power consumption by close to 50 per cent.

Siemens Enterprise Communications Pvt Ltd, Mumbai

Fax: (022) 24987303

Phone: 24987230

E-mail: asheesh.pandya@siemens-enterprise.com

Web: www.siemens-enterprise.com

POWER SUPPLY

Ultra-compact AC-DC power module

RECOM has introduced an ultra-compact converter (RAC20-SB) in the medium power range of up to 20 watts. The converter measures only 5.2x2.7x2.3 cm³, and is supplied in the same housing as the popular 10W model. It is also pin-compatible with the 5W model.

Compared to its predecessor, the power density of the module has been increased by 120 per cent to 0.6W/cm³. Efficiency varies according to output voltage limits, reaching a peak of 86 per cent at 24V. In free air convection, the ambient temperature operating range of the converters is -40°C to +70°C.

Omniscient Electronics, Bengaluru

Fax: (080) 26718151

Phone: 26718144, 26718162

E-Mail: hemanth@omniscientelectronics.com

Web: www.omniscientelectronics.net

COMPONENTS

Triac-dimmable LED driver

Ganesh Electronics has introduced an adaptive constant off-time AC-DC buck (step-down) controller designed to be compatible with triac dimmers. It provides a constant current for illuminating high-power LEDs and includes a triac



dim decoder. The dim decoder allows a wide range of LED dimming using standard triac dimmers. The high-frequency-capable architecture allows the use of small external passive components.

The controller includes a bleeder circuit to ensure proper triac operation by allowing current flow while the line voltage is low to enable proper firing of the triac. A passive PFC circuit ensures good power factor by drawing current directly from the line for most of the cycle, and provides a constant positive voltage to the buck regulator. Additional features include terminal shutdown, current limit and Vcc under-voltage lockout.

Ganesh Electronics & Electricals, Mumbai

Phone: (022) 22962306

E-mail: swarnilite@gmail.com

Web: www.swarnilite.com

16-bit SAR ADC

Linear Technology has introduced a 16-bit SAR ADC that achieves 94dB signal-to-noise ratio at sample rates up to 1 MSPs with no cycle latency. Operating from a single 5V supply and supporting a wide ± 4.096 V input range, the LTC2393-16 is well suited for many general-purpose designs that require

maximum signal swings to overcome background noise levels in demanding industrial environments.

Arrow Electronics India Ltd, Bengaluru

Fax: (80) 51127784

Phone: 51353800

High-current power MOSFETs

Texas Instruments claims to have introduced the industry's first standard-footprint power MOSFETs that dissipate heat through the top of the package for high-current DC-DC applications. DualCool NexFET power MOSFETs reduce the size of the end equipment, while providing up to 50 per cent more current through the MOSFET and improving thermal management over other standard-footprint packages. This new family of five NexFET devices allows computing and telecom system designers to use higher-current processors with expanded memory while saving board space.

Texas Instruments India

Phone: (080) 41381665

Toll free: +1-800-425-7888

E-mail: tiasia@ti.com

Web: www.ti.com

Smallest MEMS accelerometers

The new three-axis digital accelerometers from STMicroelectronics are said to combine the market's smallest footprints with a drastically reduced current consumption and enhanced functionality. The sensors measure just 2x2 mm² and consume current below 10 microamperes at a sampling rate of 100 Hz. Already lower by an order of magnitude than other devices currently in production, these values can further shrink to just a few microamperes for lower data rates. This substantial achievement is set to speed up the adoption of motion-activated features and applications in space- and power-constrained portable consumer devices, with no compromise in performance and functionality.

STMicroelectronics Marketing Pvt Ltd, Noida, Uttar Pradesh

Fax: (0120) 4243417

Phone: 4243400

Web: www.st.com/stonline