CIRKIT ELECTRO COMPONENTS PVT. LTD.

cirkit®
ELECTRO-COMPONENTS PVT. LTD.

IMPORTERS & WHOLESALE DISTRIBUTOR FOR : POWER COMPONENTS & LED DRIVERS

"Drug House" Bldg., 54-B, Proctor Road, Off. Lamington Road, Mumbai - 400 007.
Tel : 022-2387 7777 / 2380 08888. Fax : 022-2387 9335,
Mobile : 9322234370 / 9320444233 / 9322791112 / 9967683456 / 9867852000
Email : cirkitele@gmail.com / cirkitelectro@yahoo.com • Website : www.cirkitelectro.com

International IOR Rectifier

IR2101
IR2110
IR2121
IR2113
IR2130
IR2520
IR2125
IR3415
IR4905
IR1405
IR2807
IR3205
IR3710
IR634
IR344
IR2804
IR1407
IR5305
IRFB4310
IRFB4710
IRFBC30
IRFBC40
IRFBE30
IRFPG30
IRFBG30
IRFBE20
IRFBG20
IRFD120
IRFD9120
IRFD220
IRFD9220
IRFPE40
IRFPF40
IRFPE50

IRFPF50
IRFPG50
IRL3713
IRFZ24N
IRFZ34N
IRFZ44N
IRFZ48N
IRFP054
IRFP064
IRFP240
IRFP250N
IRFP250P
IRFP150N
IRFP150P
IRFP254
IRFP264
IRFP260
IRFB260
IRFP140
IRFP9140
IRFP9240
20ETS12
25TTS12
40TPS12
40EPS12
70TPS12
80EPS12
HF30PA60C
30CPQ150
30CPQ100
40CPQ100
GBPC3512
ST230C14C0
ST330C16C0

MICROCHIP

PIC12C508A I/P
PIC12F508A I/P
PIC12F675A I/P
PIC12F629A I/P
DSPIC30F2010 30 I/SP
DSPIC30F3011 20 I/SP
PIC18F452A I/SP
PIC18F252A I/SP
PIC18F2550A I/SP
PIC18F4520A I/SP
MCP604-20 I/SP
MCP3201-20 I/SP
MCP3202-20 I/SP
MCP3204-20 I/SP
MCP3208-20 I/SP
PIC16C505A04 I/P
PIC16F628A20 I/P
PIC16F690A-20 I/SP
PIC16F72A-20 I/SP
PIC16F73A-20 I/SP
PIC16F74A-20 I/SP

PIC18F4550A I/SP
PIC18F4620A I/SP
PIC18F4431A I/SP
PIC18F2431A I/SP
PIC18F458A I/SP
PIC18F488A I/SP
PIC18F6520
PIC18F6620
PIC18F6720
MCP602-20 I/SP
PIC16F76A-20 I/SP
PIC16F77A-20 I/SP
PIC16F716A-20 I/SP
PIC16F84A-20 I/SP
PIC16F871A-20 I/SP
PIC16F873A-20 I/SP
PIC16F877A-20 I/SP
PIC16F684A-20 I/SP
PIC16F819A-20 I/SP
PIC16F771A-20 I/SP
PIC16F554A-20 I/SP

POWER® INTEGRATIONS, INC.

LNK306PN
LNK305PN
LNK304PN
LNK364PN
LNK500PN
LNK501PN
LNK564PN
TOP224YN
TOP227YN
TOP234YN
TOP242YN
TOP243YN
TOP244YN
TOP245YN
TOP246YN
TOP247YN
TOP248YN
TOP249YN
TOP250YN
TOP255YN
TOP257YN

TNY267PN
TNY266PN
TNY268PN
TOP278PN
TOP234PN
TOP243PN
TOP244PN
TOP245PN
TOP414G
TNY254PN
TNY280PN
TOP210PN
TOP221PN
TOP221YN
TOP222YN
TOP222PN
TOP223YN
TOP232PN
TOP232YN
TOP233YN

Distributor :
INCHANGE® CKT

BUX80
BUX84
BUX96
BUX98
BUX98S

BUX48
BUV48
BUV48
BDX33
BDX34

BDX53
BDX54
TIP150
TIP41
TIP42
TIP47
TIP122
TIP127
MJE13005
MJE200
MJE172

2SA1943
2SC5200
BDW93
BDW94
BU508A
2N2222 (M)
2N2970 (M)
2N2369 (M)
BUT11
BUT12A
BUX80

BUX84
BUX96
BUX98
BUX98S
BUX48
BUV48
BUV48
BDX33
BDX34
BDX53
BDX54

TIP150
TIP41
TIP42
TIP47
TIP122
TIP127
MJE13005
MJE200
MJE172
2SA1943
2SC5200

BDW93
BDW94
BU508A
2N2222 (M)
2N2970 (M)
2N2369 (M)
BUT11
BUT12A

SMD ELECTRO COMPONENTS

FULL RANGE OF SMD ACTIVE & PASSIVE COMPONENTS

Authorised Distributor

leaguer	SMD E-Capacitors
KEXIN	SMD Transistors SMD LED SMD Diodes SMD Capacitors
watts	SMD Resistors

CHIP TRANSISTORS / CHIP DIODES / CHIP LED's / CHIP CAPACITORS / CHIP ICs

- CHIP RESISTORS
- CHIP RESISTOR NETWORKS
- CHIP CAPACITORS
- CHIP TANTALUM CAPACITORS
- CHIP ELECTROLYTIC CAPACITORS
- CHIP ZENERS & DIODES
- CHIP TRANSISTORS
- CHIP LED'S
- CHIP SCHOTTKY DIODES
- CHIP BRIDGE RECTIFIERS
- CHIP TRANSIENT VOLTAGE SUPPRESSORS
- CHIP IC'S
- CHIP MOSFETS
- CHIP REGULATORS
- CHIP OPTO COUPLERS
- CHIP TRIMMER CAPACITORS
- CHIP INDUCTORS
- CHIP FERRITE BEADS
- CHIP HALL SENSORS
- CHIP IR LEDS & SENSORS
- CHIP POTENTIOMETERS
- CHIP FUSES
- CHIP SWITCH
- CHIP MOV'S
- CHIP THERMISTORS
- CHIP SOLDER PASTE
- CHIP SOLDER WIRE 26 SWG.

AVX KYOCERA PHILIPS intel IOR NEC SGS-THOMSON
KEMET VISHAY Panasonic HITACHI Semiconductor ROHM TDK
National Semiconductor muRata SAMSUNG ELECTRONICS FAIRCHILD SEMICONDUCTOR ON Semiconductor MOTOROLA

54-C, Jyoti Estate, Proctor Road, Near Parijat bldg., Off. Lamington Road,
Mumbai - 400 007. INDIA. Tel. : 91-22-3240 2444 • Mob. : 93242 11912

E-mail : smdelectro@vsnl.net

RESISTORS TRUSTED WORLD WIDE

WIRE WOUND RESISTORS

HEA

Semi precision Axial type.
Power Rating : 2.5W to 17W (70°C)
Resistance Range : R025 to 70K
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Low surface temperature.
• Fire retardant • Pulse type available.

HFP

Power type PCB mounting.
Power Rating : 2W to 8W (at 70°C)
Resistance Range : R10 to 56K
Tolerances Available : 10%, 5%
Features : • Low cost. Automated assembly & wave soldering possible.
• Commercial applications.

HMV

Flat vertical mounting type.
Power Rating : 2.5W to 15W (70°C)
Resistance Range : R10 to 36K
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Ceramic legs act as heat sink.
• Slim profile. • Space saver. • Pulse type available.

Available in low ohm current sense type as HMVL series.

HANS

Resistance : 5K0, 1K125, 10K, 7K5
Tolerances Available : 20%,10% & 5%
Features : •Noise suppressor resistor to reduce RF interference.

HCP

Power Type PCB Mounting.
Power Rating : 3W to 20W (70°C)
Resistance Range : R10 to 56K
Tolerances Available : 10%, 5%
Features : •Designed for colour TV application. Adaptable to automated assembly.
•Choice of terminal stand-off heights. Choice of terminals to suit exact PCB requirements.

CURRENT SENSE RESISTORS

RL

Alloy ribbon element in cylindrical ceramic body. Axial type.
Power Rating : 0.5W to 10W (25°C)
Resistance Range : R004 to R80
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Negligible inductance.
• Replaces Moulded type.

OA/OP

Open Frame / Axial and PCB Mounting - Shunt Type.
Power Rating : 0.5W to 5W (70°C)
Resistance Range : R002 to R10
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Non insulated.
• Surge current sensing applications.

OFSC

PCB mounting.
Power Rating : 5W & 10W (70°C)
Resistance Range : R0001 to R003
Tolerances Available : 5%, 3%, 2%, 1.5%, 1%
Features : • Silicone Coated.
• Surge / current sensing applications.
• Negligible Inductance.

OF

Open Frame
PCB Mounting Punched Out Style
Power Rating : 1W to 10W (85°C)
Resistance Range : R0005 to R068
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : •Low TCR
•Tailor-made Solutions Possible

Metaphors

HI-TECH RESISTORS PVT. LTD.

AN ISO/TS 16949:2002 CERTIFIED COMPANY

Buty Compound, Mount Road Extension, Nagpur-440 001. INDIA. Tel. : +91-712-2531134, 2533269, 2553691.
Fax : +91-712-2528334, 2556351. e-mail : info@htr-india.com | www.htr-india.com