


S-18 Motorized Slotted Transmission Line Trainer



50MHz - 1.3GHz Microwave

IMPROVED



Standing Wave Pattern with
590 readings < 5mm
@ 1 mm resolution

Key Features

- ☐ **Receiver with RF Source PLL** Receiver 50-1300MHz, 100dB range, 0.1dB reso, 1.5dB accy
RF Source 50-1300MHz, 125KHz steps, 115dBuV typ in 2 bands
RS232 Serial interface for PC
Centronics for SWR hardcopy and Slotted Line control.
TDR Pulse output for TDR testing
- ☐ **Slotted Line - Motorised** 50 ohms Slotted Line with V & I probe, stepper driven by the receiver.
- ☐ **Accessories** Directional Coupler, Dual Slug Tuner, various Terminations, etc
- ☐ **Windows Software**
4 Standing Wave Patterns, SMITH Chart, R+jX, VSWR/Freq, Vi/Freq, Vr/Freq, Insertion Loss, S-Parameters (scalar) - cursor measurements etc are possible via RS232 using third party software.

SIGNET[®]
Measurable Quality

Mob: 9322509190 Fax: 24070266
Contact: M Loynmoon signet_instruments@yahoo.com
Tel: 20211079, 32523577
201/202 Champakal Ind. Est.
105, Sion (E) Mumbai 400022
www.signet-instruments.com

S-9 TRUE 2 CH 20 MHz POWERSCOPE



FEATURES

- ☐ 20MHz Power Scope
- ☐ 2 Ch Isolated Inputs
- ☐ Fully Floating Inputs
- ☐ CMRR 10000:1 at max

S-36 Microstrip Systems Trainer

VSWR-SPECTRUM-NETWORK ANALYSIS

IIT Bombay* microstrip designs

PASSIVE Devices

Power Dividers

1. Two way equal power
2. Four way equal power
3. Two way un-equal power
4. Directional Coupler
5. Two branch
6. Coupled Line
7. Rat Race Filters
8. Low Pass
9. Band Pass
10. Band Reject (Notch)

Other Components

11. Circular Ring Resonator
12. Attenuator 10dB
13. Circulator - Isolator
14. Active Devices
15. Amplifier
16. Mixer
17. Pin Diode Switch
- Terminations
Short, Open, Match & Loads

RECEIVER - Synthesized


Frequency Range: 0.85-1.3GHz
Freq & Level Resolution: 125KHz & 0.1dB resolution
Input Level: 100dB measurement range
Input Impedance: 50ohms typical
Level Accuracy: 1.5dB typical

RF SOURCE - Synthesized

Frequency Range: 0.85-1.3GHz
Resolution: 125KHz steps
Output Amplitude: 115dBuV typ into 50 ohms.
Flatness: within ± 2.5 dB wrt output at 1 GHz
Output Impedance: 50ohms

GENERAL

RS232 Interface: provided for PC connectivity and software control of the Receiver and RF Source
Centronics Interface: to connect to Epson 8300 printer for obtaining hardcopy at 850MHz



Polar Plots - E & H Plane
Cartesian Plots - E & H Plane
Directive Gain
Front Back Ratio
Sidelobe Level & Angular Position
Beamwidth - Half Power & 10dB
Current Distribution Study
Polarization Study
Verify Inverse Sqr Law axiom
Verify Reciprocity axiom
Study of Vi, Vr and VSWR
Study RF reflection and absorption

Specifications

Source : Variable source
Freq Range: 0.75 GHz to .85 GHz
Amplitude : >100 dBuV into 75 ohms.
Power Meter
Linear in dB LCD readout.
Amp range : > 50 dB
Freq Range : .75 GHz to .85 GHz
Accuracy : ± 3 dB
Display : 16 * 2 Lcd Display



LOW COST
Antenna Trainer

S-5022 SPECTRUM ANALYZER

NETWORK (Scalar) Analyzer

850 MHz



SPECTRUM Analyzer Mode

HARMONIC Mode

METER/DIGITAL/BAR Mode

Includes
AM/FM
Modulator
and
Filter Box

RF Lab EXPERIMENTS: Tuned Amp, RF Osc,
RF Xtal Osc, IF Amp, RF Mixer, RF Filter

- ☐ **S-8955** Noise Generator 5-1300 MHz 70dBuV
- ☐ **S-5022A** 1.3GHz Spectrum/Network Analyzer + Software
- ☐ **S-4068** 465MHz TV Sweep Generator + Marker (Wobbulator)
- ☐ **S-909** 1 Hz - 110 MHz Signal Generator (AM/FM SG+PS+FC)
- ☐ **S-4050** Service Test Station (AM/FM SG+PS+FG+FC)
- ☐ **S-990** 300MHz AM/FM(Stereo) Sig Gen+Sweep+Marker
- ☐ **S-945** 300 MHz AM/FM(Stereo) Synthesized Signal Gen
- ☐ **S-1611** Frequency Counter 1.3 GHz
- ☐ Enquire regarding other available Instruments

Servicing of all SIGNET instruments available.

ALL EDUCATIONAL TRAINERS AVAILABLE