

It can be used with Anritsu's handheld analysers, including the new E-series Site Master family, BTS Master, Spectrum Master and VNA Master. It is compatible with the MS271xB energy microwave spectrum analysers.

MA24126A has built-in internal and external triggers, so the sensor can conduct multi-slot measurements of TDD waveforms used in GSM, WiMAX and TD-SCDMA.

Anritsu Pte Ltd India, Bengaluru

Fax: (080) 40581301


Phone: 40581300

E-mail: ACIN-Support@anritsu.com

Web: www.anritsu.com

Power and current monitor

Linear Technology has introduced a power and current monitor for 4V to 80V systems. LT2940 provides the necessary circuits to accurately measure, monitor and control power in situations where both the current and



voltage may vary due to supply voltage uncertainty, component parametric changes, transient conditions or time-varying signals.

Unlike traditional power monitors that rely on data converters and multiplying registers to calculate power, LT2940 uses a four-quadrant analogue multiplier that results in 5 per cent power measurement accuracy and 3 per cent current measurement accuracy, ensuring that boards and systems achieve optimum power efficiency and reliability.

LT2940 is suitable for use in line cards and servers, power-sense circuit breakers, power control loops and a variety of metering applications.

Arrow Electronics India Ltd, Bengaluru

Fax: (080) 51127784

Phone: 51353800

Web: www.linear.com

COMPONENTS

JFET-input amplifiers

Texas Instruments has introduced the OPA653 and OPA659 JFET-input operational amplifiers, which provide a slew rate of up to 2675 V/ μ s. These amplifiers combine a wideband voltage



feedback amplifier with a high-impedance JFET-input stage and meet the requirements for frequency domain and FFT analysis due to their large signal bandwidth and low total harmonic distortion.

The OPA653's low overshoot and ringing are desirable in low-noise, wideband, high input impedance applications such as data acquisition cards, high-impedance probes and oscilloscope front ends. The OPA659's 350MHz high gain bandwidth optimises machine vision applications, such as broadband photodiode transimpedance amplifiers used in wafer inspection equipment.

Texas Instruments India

Phone: (080) 41381665

Toll free: +1-800-425-7888

E-mail: tiasia@ti.com

Web: www.ti.com

High-linearity gain blocks

Avago Technologies has announced three new low-noise gain blocks that can be used as a broadband gain block or radio frequency (RF) driver amplifier MMIC. Housed in a SOT-89 package measuring 4.5mm by 4.1mm by 1.5 mm, Avago's MGA-30x89 series now covers frequency bands from 40 to 6000 MHz and only requires a DC biasing match. Moreover, no additional RF matching components are required to



achieve wide bandwidth performance.

These gain blocks are ideal for designers of cellular

devices, WiMAX wireless base stations, satellite and cable TV set-top boxes, and other wireless applications that operate within the 40 to 6000MHz frequency range.

Avago Technologies

Phone: 9810803136

E-mail: sanjeet.roy@avagotech.com

Web: www.avagotechwireless.com

Sendix SIL encoders

Kübler Automation India has announced Sendix SSI/BISS absolute encoders with additional Sin/Cos output and Sendix incremental encoders in Sin/Cos version. They are available with SIL3/PLE certification.



The Sendix SIL absolute encoders obtain safe information about the absolute position; here the controller counts the incremental pulses and compares the result with the absolute position, which has also been provided by the same encoder. However, in contrast, in the case of the Sendix SIL incremental encoders, the controller monitors the validity of the analogue, 90° phase-shifted sine/cosine signals with the help of the function $\sin^2 + \cos^2 = 1$.

In addition, Sendix SIL-certified incremental and absolute encoders ensure a safe mechanical connection in the application. They feature a reliable interface and can withstand high mechanical as well as electrical loads, thanks to extra strong bearings in the Safety Lock design. With their IP67 level of protection and magnetic insensitivity, they offer all-round safety.

Kübler Automation India, Pune
Fax: (020) 22953818
Phone: 22953819
E-mail: nutan.deshpande@kuebler.com
Web: www.kuebler.com