

RJ[®] COMPLETE RANGE OF WIRES & CABLES, CABLE ASSEMBLIES

www.rjcables.com
www.rjptfe.com

PVC, PTFE, XLPE, ZERO HALOGEN, RUBBER/SILICON, PE INSULATED

- PTFE Insulated Equipment Wires as per MIL Specification
- PTFE Multicore Cables as per MIL Specification
- PTFE High Temperature Cables up to 800 Deg C
- PVC Insulated Wires & Cables to IS- 1554 Part 1
- PVC Insulated Wires & Cables to IS-694
- Elastomeric/Silicon Insulated Wires & Cables to IS-9968 Part 1

- RF Coaxial Cables
- Hookup & Flexible Wires
- Instrumentation & Control Cables
- Data Transmission Multipair Cables
- Wire Harness, Telecom Cables
- Cable Assemblies

APPLICATIONS



APPROVALS



R.J. INDUSTRIAL CORPORATION

1-2, Industrial Estate, Roorkee-247667 (Uttaranchal) India Tel.: +91-1332-268223, 265307
Fax: +91-1332-260445 E-mail: info@rjptfe.com, info@rjcables.com, rjptfe@datainfosys.net

MAJOR CUSTOMERS



* All logos and trademarks are property of their respective owner(s)

Representatives at:

- Bangalore • Hyderabad • Chennai • Trichy • Delhi
- Bhubaneswar • Bhopal • Madhya Pradesh

Authorized Sole Distributor for OWON & AEE

owon
Sole Agent for **owon**



With Autoscale



MSO

Mixed Signal Oscilloscope
(25 MHz / 100 MHz Bandwidth)
Large 8" Screen for clear view
Support both DSO & LA
Battery Operation available

PDS

Portable Digital Storage Oscilloscope
(25 MHz to 100 MHz Bandwidth)
Large 8" Screen for clear view
Battery Operation available



MINI DV 80
The Smallest Digital Video Camera
With All in One
• DV Camera
• Pen Drive
• Web Camera
• Sound Activated Camera

HDS-N

Hand Held Digital Storage Oscilloscope
(20 MHz to 100 MHz Bandwidth)
3.8" TFT Screen for clear view
2 in 1 (Multimeter Function Support)

AMP TRONICS
amplify your electronics

6-3-905/B2, Jaffer Ali Road, Somajiguda, Hyderabad- 62,
Ph : +91 40 23320240, +91 9440122805,
www.amp-tronics.com, www.owon.co.in
E-mail : info@amp-tronics.com

Friendly ARM 9 Boards



AT UNBELIEVABLE PRICE

FEATURES

CPU: 400 MHz Samsung 2440A ARM920T
RAM: 64 MB SDRAM, 32 bit 100 MHz Bus
Flash: 64 MB NAND Flash & 2 MB NOR Flash with BIOS
User Outputs: 4x LEDs
web server / USB / MMC / Audio I/O
Debug: 10 Pin JTAG (2.0mm) with touch screen
OS Support : Linux 2.6, Windows CE 5, Android*
with Technical Support

Available Range:
Mini 2440 + 3.5" LCD
Micro 2440 + 3.5" LCD
Micro 2440 + 7" LCD
Micro + VGA Module

DEALERS / DISTRIBUTORS ENQUIRIES SOLICITED